

SUBJECT INDEX

ANALOG DEVICES' PARTS INDEX

STANDARD DEVICE PARTS INDEX

▣ OP AMP APPLICATIONS

SUBJECT INDEX

- A**
- Aavid Thermal Technologies, Inc. general catalog, 7.108
 - Absorption, shielding, 7.116
 - ACCEL Technologies, Inc., 7.164
 - Accelerometer, 4.62
 - sensor, 4.3
 - Active feedback amplifier, constant current source, circuit, 6.179
 - Active inductor, design, 5.65
 - Actuator, sensor, 4.4
 - AD210:
 - key specifications and circuit, 2.45
 - three-port isolator, 2.44-46
 - AD210 Precision, Wide Bandwidth 3-Port Isolation Amplifier, 2.51
 - AD215 120kHz Bandwidth, Low Distortion, Isolation Amplifier, 2.51
 - AD215:
 - key specifications and block diagram, 2.47
 - low distortion two-port high speed isolation amplifier, 2.47
 - AD260 and AD261 High Speed Logic Isolators, 2.51
 - AD260/AD261:
 - digital isolator, key specifications, 2.50
 - digital isolator family, 2.49-50
 - one-channel schematic, 2.49
 - transformer output voltage, 2.50
 - AD275 Dual Bipolar/JFET, Audio Operational Amplifier, 3.53
 - AD503, two-chip hybrid IC op amp, schematic, H.60
 - AD506, two-chip hybrid IC op amp, schematic, H.60
 - AD506L: Economical Low-Drift FET-Input, H.69
 - AD508J, K, L IC Chopperless Low Drift Operational Amplifier Preliminary Data Sheet, H.68
 - AD509: Fast Op Amp 2 μ s to 0.01%, H.70
 - AD515, hybrid IC electrometer amplifier, H.63
 - AD526:
 - key specifications and schematic, 2.34
 - programmable precision non-inverting op amp gain stage, 2.34
 - AD526 Programmable Gain Instrumentation Amplifier, 2.41
 - AD526 Software Programmable Gain Amplifier, 2.41
 - AD545, hybrid IC electrometer amplifier, H.63
 - AD549:
 - electrometer, 1.58
 - JFET input electrometer grade op amp, with TO-99 package, 4.43
 - monolithic IC electrometer op amp, H.64
 - schematic, H.64
 - AD549K, JFET input electrometer grade op amp, 4.42
 - AD549KH, TO-99 package, 4.47
 - AD588, precision zener diode reference, 4.34
 - AD590, TO52 package, temperature transducer, 4.86
 - AD590 Two-Terminal IC Temperature Transducer, 4.92
 - AD592, TO92 package, temperature transducer, 4.86-87
 - AD594, single-chip in-amp, thermocouple cold-junction compensator, 4.77-78
 - AD595, single-chip in-amp, thermocouple cold-junction compensator, 4.77-78
 - AD600/602:
 - dual X-AMP, diagram, 6.154
 - gain as function of control voltage, plots, 6.155
 - AD620:
 - CMR as function of frequency, 2.19
 - gain-bandwidth pattern, 2.21
 - generalized external voltage protection, circuit, 7.88
 - in-amp, 4.33
 - bridge applications, 4.14
 - thin-film resistors, 7.87-89
 - monolithic IC in-amp, 2.12-15
 - preamp, 2.46
 - PSR as function of frequency, 2.19
 - schematic, 7.87
 - single-supply in-amp, 2.22-23
 - three op amp in-amp, schematic, 2.12-15
 - AD620 Low Cost, Low Power Instrumentation Amplifier, 2.29
 - AD620/AD822, single-supply composite in-amp, performance summary, 2.15
 - AD620B:
 - bridge amplifier DC error budget, 2.21
 - specifications, 2.21, 2.23
 - AD621:
 - pin-programmable-gain in-amp, 2.17
 - specifications, 2.23
 - AD622, specifications, 2.23
 - AD623:
 - in-amp
 - in bridge applications, 4.14
 - single-supply, 6.186

■ OP AMP APPLICATIONS

- architecture and key specifications, 2.16
- AD623 Single Supply, Rail-to-Rail Low Cost Instrumentation Amplifier, 2.29
- AD624C, monolithic in-amp, 2.17
- AD625, circuit, 2.39
- AD626, differential amplifier, 2.23
- AD627:
 - in-amp, in bridge applications, 4.14
 - key specifications, 2.11
 - single supply in-amp, architecture, 2.10
 - two op amp in-amp, circuit, 2.10
- AD627 Micropower, Single and Dual Supply Rail-to-Rail Instrumentation Amplifier, 2.29
- AD629:
 - CMR, 2.6
 - high common-mode input voltage difference amplifier, 2.5
 - high voltage in-amp IC, 7.81-82
- AD704:
 - quad op amp, H.54
 - super-beta input bipolar op amp, 1.35
- AD705:
 - single op amp, H.54
 - super-beta input bipolar op amp, 1.35
- AD706:
 - dual op amp, H.54
 - super-beta input bipolar op amp, 1.35
- AD707, precision amplifier, 4.22
- AD708:
 - dual op amp, H.57
 - dual precision op amp, in bridge circuit, 4.16
- AD741, precision monolithic IC op amp, H.50-51
- AD741J, K, L, S Lowest Cost High Accuracy IC Op Amp Data Sheet, H.67
- AD743:
 - FET input op amp, for high speed photodiode preamps, 4.59
 - low noise BiFET op amp, 4.64-66
 - low noise JFET IC op amp, H.65
- AD744, FET input op amp, for high speed photodiode preamps, 4.59
- AD745:
 - FET input op amp, for high speed photodiode preamps, 4.59
 - low noise BiFET op amp, 4.63-66
 - low noise JFET IC op amp, H.65
- AD768 16-Bit, 30 MSPS D/A Converter, 3.53
- AD768, 16-bit BiCMOS DAC, 3.50
- AD780, with SAR ADC, 3.44
- AD795:
 - FET input op amp, for high speed photodiode preamps, 4.59
 - low bias current FET input op amp, 7.82-83
- photodiode preamplifier
 - noise analysis, 4.52-53
 - noise gain, 4.51
- single-supply op amp, in SOIC package, 4.46
- SOIC package, 4.56
- AD795JR:
 - JFET input electrometer grade op amp, 4.42-43
 - SOIC package, 4.44
 - op amp, low input current, 4.66
 - photodiode preamp, performance summary, 4.56
 - photodiode preamplifier offset error model, 4.48
 - summary, 4.49
- AD795K, preamp with output filter and offset null option, 4.55
- AD797:
 - controlled decompensation, 6.58
 - family of distortion curves, 6.59
 - low noise op amp, 3.45
 - recommended connections, circuits, 6.58
 - THD versus frequency, plots, 6.59
- AD797/ADG412 PGA, performance summary, 2.36
- AD810, video op amp, disable mode, 6.124
- AD811:
 - current feedback amplifier, 6.50
 - current feedback video op amp, 7.148
- AD812, dual current feedback amplifier, 6.110
- AD813:
 - triple amplifier, 6.110
 - triple current feedback op amp, programmable gain video amplifier, circuit, 6.126
 - video op amp, disable mode, 6.124
- AD815 High Output Current Differential Driver data sheet, 7.108
- AD817:
 - internal capacitive load compensation, circuit, 6.88
 - unity gain inverter, 6.89
 - video op amp driver, 7.106
 - wideband in-amp, circuit, 6.184
- AD818, op amp, in simple video line receiver, circuit, 6.115
- AD820:
 - FET input op amp
 - guard techniques, 4.46
 - for high speed photodiode preamps, 4.59
 - single low-power op amp, H.65
 - single op amp, N-channel JFET input, 6.167
- AD820B, JFET input electrometer grade op amp, 4.42

- AD820BN, DIP package, 4.45
- AD822:
 - dual low-power op amp, H.65
 - dual op amp, N-channel JFET input, 6.167
 - JFET-input dual rail-to-rail output op amp, 2.14
- AD823:
 - dual 16MHz op amp, N-channel JFET input, 1.40
 - FET input op amp, for high speed photodiode preamps, 4.59
 - photodiode preamp
 - dark current compensation, 4.60
 - equivalent circuit, 4.61
 - schematic diagram, 1.41
- AD825:
 - high speed FET input op amp, 5.128-129, 5.131
 - op amp integrator, circuit and plot, 6.180
- AD828, dual op amp, 6.181
- AD829:
 - input voltage noise, 6.169
 - input voltage noise spectral density, plot, 6.166
 - wideband video amplifier, bipolar differential input, 1.34-35
- AD830:
 - active feedback amplifier, 6.179-181
 - grounded capacitor integrator, circuit and plot, 6.180
- AD830/AD8129/AD8130, active feedback amplifier, circuit, 6.117
- AD843:
 - FET input op amp, for high speed photodiode preamps, 4.59
 - high-speed FET input op amp, 6.190
- AD845:
 - BiFET 16MHz op amp, circuit, 1.111
 - FET input op amp, 6.73
 - for high speed photodiode preamps, 4.59
- AD846, current feedback op amp, diagram, 1.25
- AD847, Bode plot, 5.111
- AD847 family, folded cascaded simplified circuit, 1.110
- AD1853, stereo DAC, 3.52
- AD1853 Stereo, 24-Bit, 192 kHz, Multibit Sigma-Delta DAC, 3.53
- AD76XX, single supply SAR ADC, 3.27
- AD77XX family:
 - ADC with on-chip PGA, 2.32, 2.40
 - characteristics, 3.24
 - equivalent input circuit, 3.25
 - high resolution ADCs, 4.80-81
 - sigma-delta ADC
 - driving unbuffered, 3.25
 - high resolution, 3.24-25
- AD789X, single supply SAR ADC, 3.27
- AD813X:
 - differential ADC driver, functional diagram and equivalent circuit, 3.37
 - differential op amp, 3.51
- AD855X, chopper-stabilized op amp series, 1.32
- AD860X, CMOS op amp family, 1.47
- AD922X:
 - dual op amp, 3.37
 - SFDR, transformer coupling, 3.36
- AD976X:
 - TxDAC, 3.48-49
 - high speed output, model, 3.48
- AD977X:
 - TxDAC, 3.48-49
 - high speed output, model, 3.48
- AD7528, 8-bit dual MDAC, 5.128-129, 5.131
- AD7730:
 - 24-bit sigma-delta ADC, 4.36
 - sigma-delta high resolution measurement ADC, 4.23-24
 - on-chip PGA, circuit, 2.40
- AD7730 Bridge Transducer ADC, 4.25, 4.37
- AD7776, 10-bit ADC, 2.26
- AD7846, 16-bit converter, 2.36-37
- AD7890-10, 12-bit 8-channel ADC, circuit, 3.27
- AD8001:
 - current feedback op amp, bandwidth flatness versus feedback resistor value, plots, 6.99
 - high speed current-feedback op amp, 7.161-162
 - pulse response
 - coaxial cable driver, 6.102, 6.104
 - direct driving uncontrolled loads, 6.105
 - resistance versus load capacitance, plots, 6.86
 - RF and R_g values, for DIP and SOIC packages, table, 6.99
- AD8002, cross-coupled driver, frequency response, plots, 6.113
- AD8004, current feedback op amp, sensitivity to inverting input capacitance, plots, 6.100
- AD8010, video distribution amplifier, circuit, 6.107
- AD8011 300 MHz, 1 mA Current Feedback Amplifier Data Sheet, 1.127
- AD8011:
 - CFB op amp, noise calculations, 6.151
 - current feedback op amp
 - frequency response, 1.115
 - key specifications, 1.116
 - noise figure, input conditions, 6.151

■ OP AMP APPLICATIONS

- output noise analysis, 6.151
- AD8013:
 - 2:1 video multiplexer, circuit, 6.125
 - 3:1 video multiplexer switches, circuit, 6.125
 - triple amplifier, 6.110
 - triple current feedback op amp, 6.124
 - video op amp, disable mode, 6.124
- AD8016:
 - 20-lead PSOP3 package, 7.104-105
 - diagram, 7.105
 - IC
 - BATWING package, 7.104
 - PSOP3 package, 7.104-105
- AD8016 Low Power, High Output Current, xDSL
 - Line Driver data sheet, 7.108
- AD8016ARP, 20-lead PSOP3 package, 7.104
- AD8017 Dual High Output Current, High Speed Amplifier data sheet, 7.108
- AD8017AR:
 - op amp
 - 8-pin SOIC packaging, 7.101
 - maximum power dissipation, data sheet statement, 7.101
 - thermal rating curves, 7.103
- AD8018:
 - xDSL upstream data line driver circuit, 6.159
 - key specifications, 6.160
- AD8036:
 - clamping amplifier, 6.171-172
 - input versus output clamping, plot, 6.121
- AD8036/AD8037, clamp amplifier, equivalent circuit, 6.120
- AD8036/AD8037 Applications, 6.187
- AD8037:
 - clamp amplifier, 6.122
 - clamping amplifier, 6.171-173
 - amplitude modulator, 6.174-175
 - circuit, 6.174
 - as piecewise linear amplifier, 6.177-178
 - inverting amplifier, gain of unity, 6.172
- AD8039, settling time, plot, 1.71
- AD8047, voltage feedback op amp, video line driver, 6.106
- AD8048:
 - voltage feedback op amp
 - in lowpass filter, 1.120
 - video line driver, circuit, 6.106
- AD8055, op amp, 3.49-50
- AD8055/AD8056 Low Cost, 300 MHz Voltage Feedback Amplifiers, 3.53
- AD8057:
 - non-inverting input, 3.34
 - op amp, thermal ratings, 7.106-107
- AD8057/AD8058:
 - distortion versus output signal level, 3.24
 - high speed low distortion op amp, 3.22-24
 - key specifications, 3.23
 - distortion versus frequency plot, 3.23
- AD8057/AD8058 Low Cost, High Performance Voltage Feedback, 325 MHz Amplifiers, 3.41
- AD8058:
 - dual op amp, 3.37
 - op amp, thermal ratings, 7.106-107
- AD8074:
 - triple buffer, 6.82
 - triple video buffer, 6.98
 - video op amp, disable mode, 6.124
- AD8075:
 - triple video buffer
 - bandwidth, 1.75
 - gain and gain flatness, plots, 6.98
 - video op amp, disable mode, 6.124
- AD8116, 16x16 buffered video crosspoint switch, diagram, 6.129
- AD8129, SOIC packaging, 6.118
- AD8130:
 - common-mode rejection versus frequency, plots, 6.118
 - high impedance input, 6.119
 - in video cable-tap amplifier, circuit, 6.119
- AD8131 Low-Cost, High-Speed Differential Driver, 3.41
- AD8132 Low-Cost, High-Speed Differential Amplifier, 3.41
- AD8138:
 - differential driver amplifier, circuits, 6.114
 - op amp, in driver circuit, 3.39
 - SINAD and ENOB, 3.39
- AD8138 Low Distortion Differential Amplifier, 3.41
- AD8170, 2:1 video multiplexer, 6.128
- AD8170/AD8174/AD8180/AD8182, bipolar video
 - multiplexer, block diagram, 6.127
- AD8183/AD8185, triple 2:1 video multiplexer, block diagram, 6.127
- AD8323:
 - CATV digitally controlled variable gain amplifier
 - diagram, 6.157
 - key specifications, 6.158
- AD8350, spot noise figure and gain versus frequency, plots, 6.152
- AD8531/AD8532/AD8534 CMOS rail-to-rail op amp, schematic, 1.46
- AD8551:
 - chopper-stabilized amplifier, 7.38
 - chopper-stabilized op amp, 4.76

Index 4

- AD8551/AD8552/AD8554, chopper-stabilized amplifier, 4.22
- AD8551/AD8552/AD8554 Zero-Drift, Single-Supply, Rail-to-Rail Input/Output Operational Amplifiers Data Sheet, 1.102
- AD8571/AD8572/AD8574 chopper stabilized op amp family, characteristics, 1.100
- AD8571/AD8572/AD8574 Zero-Drift, Single-Supply, Rail-to-Rail Input/Output Operational Amplifiers Data Sheet, 1.102
- AD8601, single rail-to-rail CMOS op amp, 1.47
- AD8602:
 - CMOS op amp, with DigiTrim, 1.47
 - dual rail-to-rail CMOS op amp, 1.47
- AD8604, quad rail-to-rail CMOS op amp, 1.47
- AD8610, precision JFET op amp, 2.27
- AD9002, 8-bit flash converter, with clamp amplifier, circuit, 6.122
- AD9042:
 - 12-bit 41MSPS ADC, 3.28
 - input structure, 3.28
- AD9203 10-Bit, 40 MSPS, 3 V, 74mW A/D Converter, 3.41
- AD9203:
 - 10-bit 40MSPS ADC, 3.37-38
 - driver circuit, 3.39
 - SINAD and ENOB, 3.39
- AD9220:
 - 12-bit 10MSPS ADC, 3.16
 - SINAD/ENOB plot, 3.16
- AD9225:
 - 12-bit 25MSPS ADC, 3.12
 - 12-bit 25MSPS CMOS ADC, 3.31, 3.34-35
 - DC coupled single-ended level shifter and driver, 3.34
 - input transients, 3.35
 - waveforms, 3.35
- AD9620, closed-loop unity-gain monolithic buffer, 6.81
- AD9630, closed-loop unity-gain monolithic buffer, 6.81
- AD9632:
 - op amp, noise calculations, 3.13
 - wideband low distortion op amp, 3.12
- AD9772A 14-Bit, 160 MSPS TxDAC with 2x Interpolation Filter, 3.53
- AD22100 Voltage Output Temperature Sensor with Signal Conditioning, 4.91
- AD22103 3.3V Supply, Voltage Output Temperature Sensor with Signal Conditioning, 4.91
- AD22103, ratiometric voltage output temperature sensor, 4.89-90
- ADA830/AD8130, active feedback amplifier, 6.179
- ADC:
 - analog bandwidth, definition, 3.16
 - applications, and op amp specifications, 3.22-24
 - buffered differential input, 3.29
 - advantages, 3.29
 - schematic, 3.29
 - buffered input, 3.28
 - CMOS
 - hold-to-sample mode transition, 3.31
 - input switching transients, 3.31
 - sample-to-hold mode transition, 3.31
 - settling time, 3.32
 - SHA, 3.30
 - switched capacitor input, 3.30
 - CMOS latched buffer, 7.49
 - differential amplifiers, 3.37
 - differential input
 - drivers, 3.35
 - performance advantages, 3.35
 - transformer coupling, 3.36
 - direct-coupled single-ended single-supply driver, 3.34
 - evaluation board, 3.32
 - fast Fourier transform analysis, 3.17
 - gain and ENOB versus frequency, plot, 3.16
 - harmonic distortion, 3.17-18
 - high performance, driving, 3.21-41
 - high-impedance differential input, high transmission accuracy, 7.40
 - ideal N-bit quantization noise, 3.10
 - input-referred noise, 3.11
 - compared with op amp output noise, 3.12-13
 - input/output quantization, 3.7
 - inputs, driving, 3.21-41
 - intermodulation products, 3.19
 - logic noise, buffering, 7.48-49
 - missing codes, 3.10
 - non-monotonicity, 3.10
 - overvoltage, 3.40
 - protection circuits, 3.40
 - performance measurement, 3.14
 - quantization noise, 3.10-11
 - SFDR, 3.19
 - performance, 3.36
 - sigma-delta, high resolution, driving, 3.24-25
 - single-ended drive circuit, 3.31
 - single-ended switched capacitor, input drive circuit, 3.32
 - single-supply, scaled output, 3.27-28
 - SNR, performance, 3.36
 - specifications, 3.7-20
 - THD+N, 3.17-18
 - THD, 3.17-18
 - transfer functions, 3.8
 - two tone IMD, 3.19
 - voltage range, 3.2

■ OP AMP APPLICATIONS

- worst harmonic, 3.17-18
- ADC/DAC:
 - capacitive loads, instability, 3.44
 - decoupling, 3.43
 - reference input, driving, 3.43-45
 - voltage reference considerations, 3.43
- ADG409, CMOS switch, 2.38
- ADG438, fault-protected multiplexer, 7.81
- ADG439F, fault-protected multiplexer, 7.81
- ADG465, CMOS channel protector, 7.80
- ADG466:
 - CMOS channel protector, 7.80
 - in-amp channel-protector, circuit, 7.89
- ADG467, CMOS channel protector, 7.80
- ADG508, fault-protected multiplexer, 7.81
- ADG509F, fault-protected multiplexer, 7.81
- ADG511, single supply switch, 2.39
- ADI, birth, H.35
- ADI model 44 FET op amp, H.38
 - schematic, H.38
- ADI model 45 FET op amp, H.38
- ADI model 48 FET op amp, H.38
 - schematic, H.38
- ADI model 50 FET op amp, H.39-40
- ADI model 121 wideband DC op amp,
 - schematic, H.36-37
- ADI Modular Products, H.42
- ADI Staff, H.42
- ADI Thermal Coastline IC 8-pin SOIC package,
 - thermal rating curve, 7.104
- ADI Thermal Coastline IC package, 7.103
- ADI Website, 3.5
- ADM660, charge-pump IC, 7.61
- ADM3311E RS-232 Port Transceiver data sheet, 7.100
- ADMXXX-E, RS-232/RS-485 driver/receiver, 7.98
- ADP330X, anyCAP LDO regulator, 7.56, 7.58
- ADP3331, adjustable LDO regulator, 7.58-59
- ADP3603:
 - voltage inverter, 7.62
 - voltage regulated output device, 7.60
- ADP3604:
 - voltage inverter, 7.62
 - voltage regulated output device, 7.60
- ADP3605:
 - regulated supply inverter, circuit, 7.62
 - voltage regulated output device, 7.60
- ADP3607, voltage regulated output device, 7.60
- ADSpice model, 7.140-141, 7.145
 - frequency shaping stages, 7.143
 - op amp
 - current feedback, 7.147-148
 - noise performance, 7.145-147
 - op amp macromodels, 7.141
 - portions, 7.141
 - support, 7.152
 - voltage feedback, input and gain/pole stages, circuit, 7.142
- ADV7120/ADV7121/ADV7122, triple video DAC,
 - 6.130
- Aging, 1.58
- Air discharge, 7.91
- Air-gap discharge, ESD testing, 7.96
- Alexander power amplifier topology, 6.196
- Alexander, Mark, 6.207, 7.163
- Aliased harmonics, 3.17
- "All inverting" balanced line receiver,
 - 6.37-38
 - diagram, 6.37
- Allen, P.E., 5.133
- Allpass filter, 5.12-13
 - second-order response, 5.13
 - transfer function, 5.12
- "Almost" rail-to-rail output stages, 1.45
- Alternate balanced line receiver, 6.37
- Aluminum electrolytic capacitor:
 - OS-CON, 7.65
 - switching, 7.65
- AMP03:
 - CMR, 2.4
 - lower gain in-amp, 7.82
 - precision four-resistor differential amplifier, 2.4, 7.39
 - small-signal bandwidth, 2.4
- AMP04, in-amp, 2.39
- Amplification frequency response, RIAA equalizer, 6.17
- Amplifier:
 - applications;, 6.163-188
 - applications, 6.163-188
 - audio, 6.1-78
 - audio line stage, 6.28
 - biasing, noiseless, 6.3
 - biological, H.9
 - bridge, 4.13
 - buffer, 6.79-82, 6.79-92
 - open-loop hybrid, circuits, 6.79
 - cable-tap, 6.119
 - communications, 6.139-162
 - distortion, 6.139
 - noise, 6.139
 - specifications, 6.139-143
 - composite, 6.189-207
 - difference, 2.3-6
 - balanced, push-pull feedback, 2.6
 - CMR, 2.4
 - differential, development, H.9-12
 - differential, defined gain, precision DC, H.9
 - feedback, H.2
 - FET, 6.41
 - FET-input, voltage noise, 6.19

- forcing high noise gain, 6.84
 - high gain, general purpose, H.14
 - high speed clamping, 6.120-123
 - input versus output clamping, plot, 6.121
 - instrumentation, 2.1-30
 - see also In-amp
 - isolation, 2.43-51
 - linear-in-dB gain, 6.154
 - load capacitance, 6.83
 - long-tailed pair, H.10
 - loophrough, 6.119
 - low distortion, third order intercept
 - point, plots, 6.142
 - noise components, 6.148
 - noise figure, 6.144
 - noise resistance, 6.5
 - offset error, 4.22
 - output, cable, EMI/RFI protection, 7.129
 - output voltage phase-reversal, 7.83-84
 - overcompensation, 6.83
 - paralleled, quiet load driving, 6.168-169
 - programmable gain, 2.31-42
 - with arbitrary attenuation step size, 6.182-183
 - signal, applications, 6.1-207
 - specialty, 2.1-51
 - subtractor, 2.3-6
 - circuit diagram, 2.3
 - CMR, 2.3
 - CMR, 2.4
 - THD+N, 6.3
 - variable gain, in automatic gain control, 6.153
 - video, 6.93-138
 - voltage controlled, 6.154-156
 - Amplitude, filter, curves, 5.28-38
 - Analog bandwidth, 3.14, 3.16-17
 - Analog circuit:
 - breadboarding, 7.139-164
 - prototyping, 7.139-164
 - simulation programs, 7.139-164
 - Analog computing:
 - developments, H.13-16
 - first op amp application, H.13
 - Analog Devices Inc., birth, H.35
 - Analog Dialogue magazine, H.42
 - began, H.37
 - Analog filter, 5.1-134
 - Analog ground, 7.32-33
 - Analog-to-digital converter, see ADC
 - ANSI Standard 268-15 (Revision 1987, amendments 1989, 1990, 1991), 6.10
 - Antialias filter:
 - design, 5.113
 - specifications, 5.113
 - Artillery Director, H.13
 - Artzt, Maurice, H.5, H.7, H.17, H.26
 - Audio amplifier, 6.79-92
 - Audio balanced transmission system, diagram, 6.29
 - Audio buffer, 6.48-64
 - heat sinks, 6.49
 - high current, basic considerations, 6.48-49
 - power supply characteristics, 6.49
 - standalone, unity-gain, circuit, 6.48
 - THD+N performance, 6.50
 - Audio DAC, active lowpass filter, 3.52
 - Audio driver:
 - amplifier, test circuit, 6.52
 - capacitive loading, 6.52
 - THD+N versus frequency, plots, 6.54-55
 - Audio line driver, 6.48-64
 - design, and noise susceptibility, 6.31
 - Audio line level stages, 6.28-47
 - line amplifiers, 6.28
 - line drivers, 6.28
 - line receivers, 6.28
 - Audio line receiver, 6.30-47
 - common-mode noise susceptibility, 6.30
 - differential amplifier, diagram, 6.30
 - noise susceptibility, 6.30
 - simple line receiver, 6.33-34
 - source-load interactions in balanced systems, 6.30-32
 - CM noise, diagram, 6.31
 - Audio preamplifier, 6.1-27
 - Audio Precision System 1, test setup, 6.42
 - Audio system, differential or balanced transmission, block diagram, 6.28-29
 - Audio transformer, output balance, 6.74
 - Audion, H.1
 - Automatic gain control system, diagram, 6.153
- B**
- B4001 and B4003 common mode chokes, 7.137
 - Back-termination resistor, 6.163
 - Bainter notch filter:
 - design, 5.76
 - design equations, 5.95
 - transformation, 5.123
 - Bainter, J.R., 5.134
 - Balanced line receiver, 6.36
 - "all inverting," 6.37-38
 - diagram, 6.37
 - alternate, 6.37
 - buffered input, 6.40-41
 - CM error versus frequency, plots, 6.38, 6.42-43
 - diagram, 6.40
 - performance, 6.38-40, 6.41-43
 - TD+N, 6.39
 - Balanced transformer driver, THD+N versus frequency, plots, 6.76
 - Band reject filter, distortion, 5.109

■ OP AMP APPLICATIONS

- Bandgap, 3.43
- Bandpass filter, 5.2, 5.9-10
 - distortion, 5.109
 - peaking versus quality factor, plot, 5.10
 - phase response, 5.15-16
 - response, 5.122
 - second-order response, 5.13
 - transfer function, 5.9
 - transformation, 5.122
- "1-Bandpass" notch filter, design, 5.79
- Bandreject filter, 5.2, 5.10-11
 - response, 5.124
 - second-order response, 5.13
 - transformation, 5.123
- Bandwidth:
 - full-power, 1.68-69
 - summary, 1.69
- Bandwidth flatness, 1.75
 - op amp, 1.75
- Bardeen, J., H.41
- Bardeen, John, H.29
- Barrow, J., 6.77
- Barrow, Jeff, 7.50
- Basic single-ended mixed feedback
 - transformer driver, circuit, 6.72
- Basic transformer coupled line driver:
 - circuit, 6.69
 - THD+N versus frequency, plots, 6.70
- Baudisch, Werner, 6.77
- Baxendall, P., 6.27
- Beam force sensor, using strain gage bridge,
 - diagram, 4.30
- Bell Telephone Laboratories, H.1, H.15, H.19, H.29
 - M9 gun director, H.13
- Bench, Steve, H.27
- Bernardi, Scott, H.68
- Bessel filter, 5.3, 5.17-18, 5.21-23, 5.25
 - in CD reconstruction, 5.125-127
 - design table, 5.45
 - poles, 5.21
 - response curves, 5.34
- Best straight line, integral linearity error, 3.9
- Beyschlag Resistor Products, 7.23
- Bias current, 4.22
 - canceling effects, external to op amp, 1.60
 - very low, measurement, circuit, 1.60
- Bias current compensated bipolar input stage:
 - diagram, 1.36
 - offset current, 1.37
- Bias current compensation, using super-beta transistors, 1.35
- Biasing, H.12
- BiFET, amplifier, output voltage phase-reversal, 7.83-84
- Binary gain PGA, 2.31
 - performance summary, 2.37
 - using DAC, circuit, 2.36
- Biological amplifier, H.9
- Bipolar input, op amp, 1.34-35
- Bipolar junction transistor, see also BJT
- Bipolar (NPN-based) op amp, 1.50
- Bipolar (NPN)/CMOS (BiCOMS) op amp, 1.50
- Bipolar op amp, voltage noise, 1.77
- Bipolar transistor gain-booster input
 - composite op amp, circuit, 6.197
- Bipolar transistor input stage, diagram, 1.34
- Bipolar video multiplexer, block diagrams, 6.127
- Bipolar/JFET (BiFET) op amp, 1.50
- Biquadratic filter:
 - design, 5.73
 - design equations, 5.91-92
- Birt, David, 2.6, 2.29, 6.36, 6.47
- Bishop, P.O., H.12, H.24
- BJT:
 - input device, rectification, 7.123
 - RFI rectification, 7.123-125
 - see also Bipolar junction transistor
- Black, Harold, H.15
- Black, Harold S., H.3-4, H.6
- Black, H.S., H.6
- Black's feedback amplifier, H.4
- Blattner, D.G., H.25
- Bleaney, B.I., 7.23, 7.50
- Blinchikoff, H.J., 5.133
- Blood, William R. Jr., 6.91, 6.137, 7.138
- Blumlein, A.D., H.9, H.23
- Boctor notch filter:
 - design, 5.77-78
 - highpass, design equations, 5.97-98
 - lowpass, design equations, 5.96
- Boctor, S.A., 5.134
- Bode plot, 1.13-14, 1.73, 1.106, 1.114, 1.118, 1.120, 4.57, 5.111, 6.203
 - equations, 4.50
 - log-log scale, 4.53
 - noise gain, 4.50
- Bode, Hendrick, H.5, H.6-7, H.15, 1.20
- Bogatina, Eric, 7.137, 7.138
 - Website, 7.138
- Boghosian, W.H., H.25
- Boghosian, William, H.13
- Boltzmann's constant, 1.76, 1.84, 1.105, 4.52, 4.84, 6.144
- Bootstrapping, 7.82
- Bore, G., 6.10
- Borlase, Walter, 1.20, 2.29, 6.47
- Bourdon tube, 4.32
- Bowers, Derek, H.54, H.59, H.71, 6.91, 6.207, 7.163
- Boyle, 7.163

- Boyle model, 7.141, 7.145
Bradley-McCoy circuit, H.18
Bradley, F., 6.27
Bradley, Frank, H.18
Bradley, Frank R., H.26
Brant, James, 1.1
Brattain, Walter, H.29
Brattain, W.H., H.41
Breadboarding:
 op amp functions, 7.139-164
 and parasitics, 7.150-151
 techniques, 7.153-162
 versus simulation, 7.148-149
Bridge:
 AC excitation, offset voltage
 minimization, 4.23
 all-element varying, 4.11
 circuit, 4.33
 amplifier
 in-amp, circuit, 4.14
 single op amp, circuit, 4.13
 circuit, 4.7
 configurations, 4.11
 output voltage, 4.9
 design considerations, 4.12
 linearization, using op amps, 4.16
 measurement, offset voltage, 4.22
 nonlinearity, 4.10, 4.14-15
 null, 4.9
 operation, 4.8
 output
 amplifying and linearizing, 4.13-17
 linearization, 4.14
 remote
 3-wire sensors, 4.19
 4-wire current-driven, 4.21
 4-wire sensors, 4.20
 6-wire sensors, 4.20
 buffer, 4.21
 driving, 4.18-21
 problems, 4.18
 using Kelvin sensing, 4.20
 wiring resistance errors, diagram,
 4.18
 sensitivity, 4.10
 and CMR, 6.32
 gain, 4.15
 sensor resistances, listing, 4.7
 signal conditioning circuit, 4.33-36
 single-element varying, 4.10
 linearization, 4.15-16
 output amplification, 4.13
 two-element varying, 4.10-11
 current-driven, linearization, 4.17
 voltage-driven, 4.16-17
 varying, diagram, 4.11
 voltage output, 4.12
Brokaw cell, sensor, 4.85
Brokaw, Adrian P., H.70, 4.91-92
Brokaw, P., 6.77
Brokaw, Paul, 4.91, 6.77, 6.207, 7.50, 7.73,
 7.138
Brown, Thomas, H.31
Bruner, Eberhard, 6.187
Bryant, James, 1.23, 1.31, 1.53, 2.1, 2.31,
 2.43, 4.1, 4.69, 7.1, 7.25, 7.75, 7.99,
 7.109, 7.137, 7.139
Bryne, Mike, 7.100
Buchanan, James E., 7.22
Budak, A., 5.133
Buderi, Robert, H.25
BUF03, open-loop IC buffer, circuit diagram,
 6.80
BUF04:
 closed-loop unity-gain monolithic buffer,
 6.81-82
 unity-gain buffer amplifier, 6.22
Buffer:
 amplifier, 6.79-82, 6.79-92
 audio, THD+N performance, 6.50
 closed-loop unity-gain monolithic,
 diagrams, 6.81
 dual amplifier, 6.50-51
 circuit, 6.51
 THD+N versus frequency, plots, 6.51
 negative resistance, 6.185
 circuits, 6.185
 open-loop, disadvantages, 6.81
 single-supply RGB video, 6.130-131
 standalone, unity-gain, circuit, 6.48
 unity-gain stable voltage/current
 feedback op amp, 6.82
Buffered input balanced line receiver, 6.40-
 41
 CM error versus frequency, plots, 6.42-43
 diagram, 6.40
 performance, 6.41-43
Buffering, DAC, with op amps, 3.47
Buried zener, 3.43
Burkhardt, Andrew, 7.137
Burr-Brown Applications Staff, H.41
Burr-Brown Research Corporation, H.31, H.35,
 H.63
Burr, Robert Page, H.31
Burton, L.T., 5.134
Burwen, Dick, H.36-37, H.42, H.43, H.69
Butler, Jim, H.62
Butterworth filter, 5.3, 5.17, 5.19, 5.23,
 5.25
 design table, 5.39, 5.114
 response curves, 5.28, 5.113
 transformation, 5.119
Buxton, Joe, 6.91, 7.75, 7.99, 7.137, 7.139,
 7.163
C
CA3130, H.61

■ OP AMP APPLICATIONS

- CA3140, H.61
- Cable:
 - coaxial
 - bandwidth flatness, 6.103
 - losses, 6.101
 - resistive load, 6.101
 - shielding, 7.121
 - driving, behavior, 6.101
 - electrical length, 7.118-119
 - and EMI/RFI, 7.118-121
 - grounding, 7.119
 - hybrid grounding, shields, 7.120
 - shielded, impedance-balanced drive, 7.121
 - twisted pair, ground loops, 7.119
- Cable modem, 6.157
- Cable-tap amplifier, 6.119
- Caddock firm, resistors, 6.34
- Cadigan, John, H.37
- Capacitance, parallel plates, 7.46
- Capacitive coupling, equivalent circuit model, 7.47
- Capacitive load:
 - active (in-the-loop), circuit, 6.87
 - audio driver, 6.52
 - driving, 6.79-92, 6.82-92, 6.83-90
 - forced high-loop noise gain, 6.83
 - and frequency response, 6.86
 - internal compensation, disadvantages, 6.89
 - open-loop series resistance, 6.85
 - overcompensation, 6.83
 - "passive" compensation, 6.85
- Capacitive noise, 7.47
- Capacitor, 7.64-67
 - ceramic, 7.7, 7.65, 7.66
 - classes, 7.64-65
 - comparison chart, 5.104
 - critical component assembly, 7.6-8
 - decoupling, 7.19
 - dielectric, 7.64-65
 - dielectric absorption, 7.2-4
 - open-circuit voltage, 7.3
 - dissipation factor, 7.4-5
 - electrolytic, 7.7-8, 7.65
 - equivalent circuit, 5.103, 7.66
 - film, 7.65, 7.65-66
 - filter problem, 5.101-105
 - high-K ceramics, 7.4
 - materials, 7.4-5
 - mica, 7.7
 - multi-layer ceramic, 7.57
 - non-ideal equivalent circuit, parasitic elements, 7.2
 - parasitics, 7.4-5, 7.66
 - polycarbonate, 7.4, 7.7
 - polyester, 7.7
 - polypropylene, 7.7
 - polystyrene, 7.7
 - selection criteria, 7.7
 - Teflon, 7.7
 - temperature coefficient, 7.5-6, 7.6
 - tolerance, 7.5-6
 - type, 7.2
 - voltage coefficient, 7.6
- Capsule Listing of Analog Devices Op Amps, H.42
- Card-entry filter, 7.69
- Cartridge frequency response, RIAA equalizer, 6.17
- Cascaded NPN differential pair topology, in op amp, H.32
- Cauer filter, 5.23-24
- Cauer, W., 5.133
- CD reconstruction filter, 5.125-127
 - performance, 5.127
 - transformation, diagrams, 5.126
- Ceramic capacitor, 7.66
- Ceramic dielectric, 5.102, 5.104
- Channel protector, advantages, 7.80
- Charge amplifier:
 - basic circuit, 4.62
 - basic configurations, 4.63
- Charge transducer, types, 4.62-63
- Charge-pump voltage converter, 7.59-60
 - characteristics, 7.60
 - unregulated inverter and doubler, 7.61
 - voltage doubler, 7.59-60
 - voltage inverter, 7.59-60
- Charged Device Model, for ESD, 7.95
- Chebyshev filter, 5.7, 5.17-18, 5.19-23, 5.54, 5.57
 - bandwidths, 5.21
 - design tables, 5.40-44
 - inverse, 5.25
 - lowpass, 5.51
 - poles, 5.20
 - response curves, 5.29-33
 - stopband, maximally flat delay, 5.25
 - transformation, 5.119-120
- Checkovich, Peter, 6.137, 6.187
- Chemical sensor, 4.39
- Chesnut, Bill, 7.73
- Chestnut, Bill, 4.5
- Chip Center's "Signal Integrity" page, 7.138
- Choosing and Using N-Channel Dual J-FETs, 6.207
- Chopper stabilized amplifier, 1.98-100
 - noise, 1.101
- Christie, S.H., 4.8
- Chrominance, 6.96
- Circuit:
 - digital, noise, 7.31
 - peaking, 5.59
 - performance, summary, 4.56
- Clamping, input versus output, 6.121
- Clamping diode leakage, 7.77-78

- Clarke, Bob, 6.161
- Classic Cameo, H.72, 2.30
- Clelland, Ian, 7.73
- Closed loop bandwidth, 4.51
 - voltage feedback op amp, 1.107
- Closed loop error, calculation, 1.64-65
- Closed loop gain:
 - calculation, 1.65
 - nonlinearity, calculation, 1.67
 - uncertainty, 1.65
- Close, JoAnn, H.62, H.64, H.70, H.71, 6.187
- CM, see also common mode
- CM over-voltage protection, using high CM in-amp, 7.81-82
- CMOS DAC Application Guide, 5.134
- CMOS device, video use, disadvantages, 6.127
- CMOS latched buffer, 7.49
- CMOS switch, in multiplexer, 3.26
- CMR:
 - bridge, 4.13
 - in-amp, 2.2, 2.18
 - resistor, worst case, 6.34
 - subtractor amplifier, 2.4
- CMRR:
 - measurement, 1.90
 - op amp, 1.89-92
 - test circuit, 1.90
 - no precision resistors, 1.90
- Coaxial cable:
 - bandwidth flatness, 6.103
 - driver, pulse response, 6.102
 - losses, 6.101
 - resistive load, 6.101
- CODECs, 6.4
- Cohen, Avner, 7.99
- Cold-junction compensation, thermocouples, 4.70-76
- Colloms, M., 6.27
- Color:
 - intensity, 6.96
 - saturation, 6.96
 - subcarrier, amplitude, 6.96
- Common mode, see also CM
- Common mode choke, 7.114
- Common mode over-voltage protection, using CMOS channel protectors, 7.80-82
- Common mode rejection:
 - calculation, 6.31
 - see CMR
- Common mode signal, 2.2
- Common mode voltage:
 - op amp, 7.75-77
 - and signal voltage, rule, 2.13
- Common-mode feedback, H.9
- Common-mode rejection, H.9
- Communication network, available power gain, circuit, 6.145
- Communications amplifier, 6.139-162
- 1 dB compression point and intercept points, plots, 6.141
- distortion, 6.140-143
- dynamic range specifications, 6.139
- intermodulation distortion, 6.140
- multitone power ratio, 6.143
- noise, 6.144-152
- noise figure, 6.144
- SFDR, 6.143
- Compatibility of Analog Signals for Electronic Industrial Process Instruments, 4.5
- Complementary bipolar (CB) op amp, 1.50
- Complementary bipolar/CMOS (CBCMOS) op amp, 1.50
- Complementary bipolar/JFET (CBFET) op amp, 1.50
- Complementary common-emitter/common-source output stages, diagrams, 1.45
- Complementary MOSFET (CMOS) op amp, 1.50
- Composite amplifier, 6.189-207
 - bipolar transistor gain-boosted input, circuit, 6.197
 - DC performance limitations, 6.203
 - definition, 6.189
 - gain-boosted input, 6.197-205
 - gain/phase versus frequency, plots, 6.198
 - high voltage boosted rail-rail, 6.195
 - JFET transistor gain-boosted, 6.201-203
 - gain/phase versus frequency, plots, 6.202
 - low noise gain-boosted input, 6.200
 - circuit, 6.200
 - low noise JFET gain-boosted input, 6.204-205
 - gain/phase versus frequency, plots, 6.205
 - low voltage single-supply to high output voltage interface, 6.191-192
 - circuit, 6.191
 - multiple op amp, 6.190-192
 - "nostalgia" vacuum tube input/output, 6.206
 - circuit, 6.206
 - slew rate, 6.199
 - time domain response, 6.203
 - two op amp, 6.190
 - low noise/low drift, circuit, 6.190
 - voltage-boosted output, 6.193-196
 - rail-rail output driver, 6.193-195
- Composite current boosted driver, 6.62-64 circuits, 6.62-64
- Composite gain response, multiple-slope response, 6.202
- Computer Labs, H.39-40

■ OP AMP APPLICATIONS

Conant, James, 2.51
Conductivity, infinite ground, 7.29
Conductor, resistance, 7.26-27
Connelly, J.A., 7.99
Consumer equipment line driver, 6.55-56
 circuit, 6.56
 THD+N performance, 6.56
Contact discharge, 7.91
 ESD testing, 7.96
Controlled decompensation, 6.58
Counts, Lew, H.43, H.62, H.69, H.70, H.71,
 2.29, 6.47, 6.187, 7.22, 7.99, 7.137
Cross-coupled differential driver, 6.67-68,
 6.111-113
 circuit, 6.67
Cross-coupled in-amp:
 circuit, 6.186
 for increased CMR, 6.186
Crosspoint switches and integrated video
 multiplexers, 6.127-129
Crosstalk, 7.112
 multiplexer, 3.26
Culmer, Daniel D., H.61, H.69
Current boosted buffered line driver, 6.60-
 61
 circuit, 6.60
 THD+N versus frequency, plots, 6.61
Current feedback:
 in macromodel, 7.141
 using vacuum tubes, 1.26-28
Current feedback op amp, 1.24-25, 1.113-117
 basics, 1.24-25
 closed-loop bandwidth, 1.74
 comparison with voltage feedback op amp,
 1.124-125
 in current-to-voltage converter, 1.122
 frequency response, 1.74
 plots, 1.74
 input capacitance sensitivity, 1.123
 input impedance, diagram, 1.62
 low inverting input impedance, 1.123
 model, 7.147-148
 open-loop transimpedance gain, 1.24
Current noise gain:
 op amp, 1.118-119
 definition, diagram, 1.119
Current output temperature sensor, 4.86-88
Current-to-voltage converter:
 high speed, inverting input capacitance
 effects, 1.120-124
 using current feedback op amp, 1.122
Cutoff frequency, 5.2
 filter, 5.3

D

DAC:
 audio, lowpass filter, 3.52
 buffered voltage output, 3.47

buffering, by differential op amp, 3.51
control word
 and frequency response, 5.129
 and gain variation, 5.130
 and quality response, 5.130
differential to single-ended conversion,
 3.48-50
filtered output, 3.2
input/output quantization, 3.7
non-monotonicity, 3.9
output, buffering, 3.47-54
performance measurement, 3.14
quantization noise, 3.10-11
specifications, 3.7-20
transfer functions, 3.8
transformer, 3.49
DAC programmed PGA, 2.36-37
Damping ratio, filter, 5.7
Daniels, R.W., 5.133
Dark current, 4.41, 4.59
Darlington buffer, H.38
Darlington connection, 7.55
Darlington, Sydney, H.13
Data acquisition, multiplexer, fast
 settling op amp, 3.27
Data converter:
 applications, 3.8
 characteristics, 3.3
 datasheets, 3.4
 dynamic performance
 quantifying and measuring, 3.14
 specifications, 3.14
 integral linearity, 3.9
 parameters, Websites, 3.4
 performance, 3.3
 requirements, 3.3-4
 sampling and reconstruction, 3.8
 test setup, performance measurement, 3.14
 transient currents, 3.4
 trends, 3.3-5
Data Sheet for Model K2-W Operational
 Amplifier, H.27
Davis, William, H.51, H.67
DC-coupled active feedback RIAA moving
 magnet preamp, circuit, 6.18
De Forest, Lee, H.1, H.6
De-compensated op amp, 1.107
Deadbug prototyping, 7.153-155
 "bird's nest" construction, 7.154
Decade gains, PGA, 2.31
Decoupling, 3.43
 capacitor, 7.19
 op amp, techniques, 1.92
 and power supplies, 1.92
Delay constant, microstrip, 7.133
Delyiannis, T., 5.133
Demrow, Robert, 2.29, 2.30, 6.47, 6.207
Derating curves, 7.103

- Development of an Extensive SPICE Macromodel for "Current-Feedback" Amplifiers, 7.163
 - Dielectric:
 - absorption, 7.2-4
 - material characteristic, 7.4
 - PCB, 7.45
 - sample-hold errors, 7.3
 - hysteresis, 7.2-3
 - types, 7.6
 - Difference amplifier, 2.3-6
 - Differential circuit, 7.28
 - Differential current-to-differential voltage conversion, 3.51
 - Differential DC coupled output, 3.49-50
 - Differential driver:
 - cross-coupled, 6.111-113
 - advantages, 6.111-113
 - circuit, 6.111
 - fully integrated, 6.114
 - inverter-follower, circuit, 6.109
 - Differential gain, color video, 6.96
 - Differential input ground isolating amplifier, circuit, 7.39
 - Differential line driver, 6.65-68
 - cross-coupled, 6.67-68
 - circuit, 6.67
 - "inverter-follower"
 - circuit, 6.65
 - THD+N versus frequency, plots, 6.66
 - Differential line driver/receiver, 6.108-119
 - Differential line receiver:
 - 4-resistor, 6.115-116
 - circuit, 6.115-116
 - active feedback, 6.117-119
 - CM rejection, 6.117
 - balanced feedback, 6.36
 - Differential non-linearity, 3.9
 - see also DNL
 - Differential pair biasing, H.10
 - Differential phase, color video, 6.96
 - Differential transformer coupling, 3.49
 - Differential-mode filter, 7.114
 - Digital audio filter, 5.125-127
 - Digital ground, 7.32-33
 - Digital isolation techniques, 2.48-50
 - application, 2.50
 - using LED/photodiode optocouplers, 2.48
 - using LED/phototransistor optocouplers, 2.48
 - Digital signal processor, see DSP
 - Digital-to-analog converter, see DAC
 - Digitally programmable state variable filter, 5.128-131
 - circuit diagram, 5.129
 - Digitizing RGB signals, using ADC and 4:1 multiplexer, diagram, 6.128-129
 - DigiTrim, 1.47
 - advantages, 1.49
 - Dinsmore, Kristen, H.70
 - Diode:
 - clamping, reverse bias current characteristics, 7.77
 - clamps, 2.24
 - p-n junction, rectifiers, 7.123
 - Discrete multitone signal, in frequency domain, plot, 6.159
 - Discrete transistor, for op amp, H.30
 - Displacement transducer, 4.30
 - Dissipation factor, 7.5
 - Distortion curves, for AD797, 6.59
 - DNL, excess in ADCs, missing codes, 3.10
 - Dobkin, Bob, H.66
 - Doebelin, Ernest O., 4.37
 - Doeling, W., 7.22, 7.50
 - Dos Santos, Francisco, H.65
 - Dostal, J., 1.93
 - Dostal, Jiri, 4.67
 - Doubler charge-pump voltage converter, 7.61
 - DPAD1, dual low leakage diode, 7.83
 - Drift, 1.58
 - Driver, audio line stage, 6.28
 - Driving capacitive load, 6.82-92
 - Dropout voltage, 7.52
 - Dual 16MHz Rail-Rail FET, H.70
 - Dual amplifier bandpass filter:
 - design, 5.74
 - design equations, 5.93
 - Dual amplifier buffer, 6.50-51
 - circuit, 6.51
 - THD+N versus frequency, plots, 6.51
 - Dual FET, 3 to $\pm 18V$, H.70
 - Dual RGB source video multiplexer, 6.128
 - Dual-supply low frequency rail
 - bypass/distribution filter, circuit, 7.70
 - Dobkin, Bob, H.70
 - Dummer, G.W.A., 7.23, 7.50
 - Duncan Munro's SPICE vacuum tube models, 6.207
 - Duncan, B., 6.27
- E**
- Early effects, 4.84
 - Edson, J.O., 1.29
 - EEPROM trimming, advantages, 1.49
 - Effective number of bits, see ENOB
 - Effective series inductance, 7.5
 - Effective series resistance, 7.5
 - Effective voltage gain, transformer, 6.6
 - EIAJ ED-44701 Test Method C-111, 7.99
 - Electret microphone preamp interface, 6.4
 - circuit, 6.4
 - Electrical Gun Director Demonstrated, H.25
 - Electrolytic capacitor, 5.102, 5.104, 7.7-8
 - advantages, 7.65
 - equivalent series resistance, 7.67

■ OP AMP APPLICATIONS

- finite ESR, 7.67
 - general purpose aluminum, 7.65
 - OS-CON, 7.65
 - switching, 7.65
 - impedance curves, 7.67
 - leakage errors, 3.45
 - tantalum, 7.65
 - Electromagnetic compatibility, definition, 7.109
 - Electrometer, 1.58
 - Electrometer IC op amp, H.63-64
 - Electrostatic discharge:
 - damage, 7.92
 - failure mechanisms, 7.92
 - models and testing, 7.95-98
 - see also ESD
 - sources, 7.91
 - voltage amounts generated, 7.90
 - Elliptical filter, 5.23-24
 - definition, 5.24
 - lowpass, 5.54
 - Embedding traces, in printed circuit board, 7.135-136
 - EMI/RFI:
 - and amplifier outputs, 7.129
 - cables, 7.118-121
 - and circuitry, 7.109-138
 - coupling paths, 7.110-112
 - noise coupling mechanisms, 7.110-111
 - reducing common-impedance noise, 7.110-111
 - summary, 7.111
 - impedance mismatch, 7.116
 - maximum radiation, opening, 7.117-118
 - mechanisms, 7.110-112
 - noise filters, for op amp circuits, 7.126
 - noise sources, 7.110
 - printed circuit board design, 7.130-136
 - reduction
 - passive components, 7.114-115
 - shielding, 7.115-121
 - system susceptibility, 7.115
 - susceptibility, 7.109
 - reduction, 7.115
 - Emission, spurious, 7.109
 - Emitter degeneration, 1.108
 - End point, integral linearity error, 3.9
 - ENOB, 3.14, 3.15-16
 - calculation, 3.15
 - Equiripple error:
 - filter, 5.22
 - design tables, 5.46-47
 - linear phase, response curves, 5.35-36
 - Equivalent noise bandwidth, 1.82-83
 - calculation, 4.61
 - Equivalent series inductance, 7.2
 - Erdi, G., 6.27
 - Erdi, George, H.49, H.53, H.55-56, H.58,
 - H.61, H.67, H.68, H.71, 1.51, 6.91
 - Eric Bogatin Website, 7.138
 - Erismann, Brian, 7.73
 - ESD:
 - prevention, summary, 7.98
 - see also electrostatic discharge
 - test circuits and values, 7.97
 - test methods, comparison, 7.96-97
 - test waveforms, 7.97
 - ESD Association Draft Standard DS5.3, 7.99
 - ESD Association Standard S5.2, 7.99
 - ESD Prevention Manual, 7.99
 - ESD-sensitive device:
 - handling techniques, 7.93-94
 - packaging and labeling, 7.92
 - Evaluation board, for prototyping, 7.160-162
 - Evolution from Operational Amplifier to Data Amplifier, 2.30
 - Excess noise, resistors, 7.13-14
 - Exponential amplifier, X-AMP, 6.154
 - External current, 7.29
 - External series resistors, 2.24
- ## F
- Fagen, M.D., H.24
 - Fair-Rite ferrites, PSpice models, 7.68
 - Fair-Rite Linear Ferrites Catalog, 7.73
 - Fairchild Semiconductor Corporation, H.29-30, H.45, H.48, H.49, H.55-56, H.61
 - Faraday shield, 6.73-74, 7.18, 7.46-47, 7.49, 7.112
 - floating, 7.48
 - impracticality, 7.48
 - operational model, 7.47
 - Farnsley, Larry, H.53
 - Fast FET Op Amp, H.69
 - Fast Fourier transform, 3.2, 3.14
 - Fast Op Amp, High Performance, Low Power, Low Cost, H.71
 - FDNR filter:
 - in CD reconstruction, 5.125-127
 - design, 5.66, 5.117
 - op amp limitations, 5.107
 - Feedback transformer coupled line driver, 6.71-76
 - Ferrite:
 - beads, 7.68
 - characteristics, 7.68
 - filter
 - inductor, 7.68-69
 - local high frequency
 - bypass/decoupling, 7.71
 - functions, 7.68
 - impedance, 7.68
 - FET, RFI rectification, 7.124-125
 - The FET Constant-Current Source/Limiter, 6.207
 - FET input op amp, 1.38-39

- filter distortion, 5.107
- low-noise, in high-output moving coil microphone preamp, 6.22
- lower current noise, 1.38
- rectification, 7.123
- FET-Input AD545, H.69
- FET-Input ICs Can Slew at 50V/ μ s, H.69
- FET-Input Op Amp Has Lowest Combined V and I Noise, H.70
- Fieldbuses: Look Before You Leap, 4.5
- 5751, H.22
- Film capacitor, 7.65-66
 - linear temperature coefficient, 5.102
- Filter:
 - 60Hz notch, 5.131-132
 - schematic, 5.132
 - "1-bandpass" notch, 5.79
 - active topology, using integrator design, 6.180
 - all-pole, comparison, 5.23
 - allpass, 5.12-13, 5.57-58
 - second-order response, 5.13
 - transfer function, 5.12
 - amplitude curves, 5.28-38
 - analog, 5.1-134
 - anti-aliasing, 3.2
 - positioning, 3.13
 - applications, 5.1
 - Bainter notch, 5.76
 - design equations, 5.95
 - transformation, 5.123
 - bandpass, 5.2, 5.5, 5.9-10
 - peaking versus quality factor, plot, 5.10
 - phase response, 5.15
 - response, 5.122
 - second-order response, 5.13
 - transfer function, 5.9
 - transformation, 5.122
 - bandreject, 5.2, 5.10-11
 - response, 5.124
 - second-order response, 5.13
 - transformation, 5.123
 - bandwidth, 5.9
 - Bessel, 5.3, 5.17-18, 5.21-23, 5.25
 - in CD reconstruction, 5.125-127
 - design table, 5.45
 - poles, 5.21
 - response curves, 5.34
 - biquadratic, 5.73
 - design equations, 5.91-92
 - Boctor notch, 5.77-78
 - highpass, design equations, 5.97-98
 - lowpass, design equations, 5.96
 - buffers, 5.59
 - Butterworth, 5.3, 5.17, 5.19, 5.23, 5.25
 - design table, 5.39
 - transformation, 5.119
 - Cauer, 5.23-24
 - CD reconstruction, 5.125-127
 - Chebyshev, 5.7, 5.17-18, 5.19-23, 5.54, 5.57
 - bandwidths, 5.21
 - design tables, 5.40-44
 - inverse, 5.25
 - lowpass, 5.51
 - poles, 5.20
 - response curves, 5.29-33
 - stopband, maximally flat delay, 5.25
 - transformation, 5.119-120
 - circuit quality factor, 5.59
 - component quality factor, 5.59
 - cutoff frequency, 5.2, 5.3, 5.7-14
 - damping ratio, 5.7
 - definition, 5.1
 - denormalization, 5.26
 - design, 5.59-100, 5.113-132
 - active inductor, 5.65
 - frequency dependent negative resistor (FDNR), 5.66-67
 - general impedance converter, 5.64
 - integrator, 5.63
 - passive LC section, 5.61-63
 - problems, 5.101-112
 - single pole RC, 5.60
 - digitally programmable state variable, 5.128-131
 - circuit diagram, 5.129
 - dual amplifier bandpass, 5.74
 - design equations, 5.93
 - effect of nonlinear phase, 5.16
 - elliptical, 5.23-24
 - definition, 5.24
 - lowpass, 5.54
 - equiripple error
 - design tables, 5.46-47
 - linear phase, response curves, 5.35-36
 - equivalent series resistance, 7.65
 - FDNR
 - in CD reconstruction, 5.125-127
 - design, 5.117
 - first order allpass, 5.80
 - design equations, 5.99
 - frequency dependent response, 5.5
 - frequency transformation, 5.51-58
 - algorithm, 5.53-54
 - Gaussian, 5.22
 - design tables, 5.48-49
 - response curves, 5.37-38
 - group delay curves, 5.28-38
 - harmonics, 5.14
 - highpass, 5.2, 5.5, 5.8
 - from Sallen-Key, transformation, 5.120
 - peaking versus quality factor, plot, 5.8

■ OP AMP APPLICATIONS

- phase response, 5.14-16
- response, 5.121
- second-order response, 5.13
- ideal, 5.2
- impulse response curves, 5.28-38
- in-amp
 - common-mode/differential-mode RC EMI/RFI, 7.127
 - family, circuit, 7.128
- inductor, 7.68-72
- key parameters, 5.3
- limitations of op amps, 5.106-107
- linear phase with equiripple error, 5.22
- local high frequency bypass/decoupling, 7.71
- lowpass, 5.2
 - from Sallen-Key, transformation, 5.119
 - peaking versus quality factor, plot, 5.7
 - phase response, 5.14-16
 - response, 5.26-49, 5.121
 - second-order response, 5.13
 - to allpass, frequency transformation, 5.57-58
 - to bandpass, frequency transformation, 5.52-55
 - to bandreject, frequency transformation, 5.55-57
 - to highpass, frequency transformation, 5.51-52
 - to notch, frequency transformation, 5.55-57
- lowpass prototype, 5.8
- minimizing EMI, 7.114
- minimum passband attenuation, 5.3
- multiple feedback, 5.70-71
 - bandpass, design equations, 5.87
 - design, 5.116
 - highpass, design equations, 5.86
 - lowpass, design equations, 5.85
 - transformation, 5.121
- notch, 5.2, 5.10-11
 - second-order response, 5.13
 - standard, lowpass, and highpass, plot, 5.11
- order, 5.3, 5.113
- passband, 5.2
- passband gain, 5.8
- passband ripple, 5.3
- PC card entry, 7.69
- performance, and op amp accuracy, 5.117
- phase response, 5.14-16
- power supply, 7.64
- prototype response curves, 5.26-49
- quality factor, 5.7
- rail bypass/distribution, 7.70
- realizations, 5.59-100
- RLC circuit, 5.6

- S-plane, 5.5-6
- Sallen-Key, 5.67-69
 - bandpass, design equations, 5.84
 - design, 5.115-117
 - highpass, design equations, 5.83
 - lowpass, design equations, 5.82
 - to lowpass, 5.119
 - transformation, 5.119-120
- second order allpass, 5.80
 - design equations, 5.100
- single pole, design equations, 5.81
- standard responses, 5.19-50
- state variable, 5.72-73
 - design, 5.116
 - design equations, 5.88-90
- step response, 5.18
 - curves, 5.28-38
- stopband, 5.2
 - frequency, 5.3
- switched capacitor structure, 5.115
- time domain response, 5.17-18
 - impulse response, 5.17-18
- transfer function, 5.5-16
- transformations, 5.119-124
- transitional, 5.22
- twin T notch, 5.75
 - design equations, 5.94
 - schematic, 5.132
- voltage standing wave ratio, 5.24
- First Monolithic FET Op Amp with $1\mu\text{V}/\text{C}$ Drift, H.69
- First order allpass filter:
 - design, 5.80
 - design equations, 5.99
- Fitchen, F.C., 6.10
- Flash converter, with clamp amp input protection, 6.122-123
- Flat pulse generator, 1.71
- Fleming diode, H.1
- Fleming, J.A., H.6
- Fleming, Tarlton, 7.22
- Flexible voltage follower protection circuit, 7.78-79
- Flicker noise, 1.79, 7.146
- Flow:
 - defining, 4.32
 - measurement, 4.27-37
- The Flow and Level Handbook, 4.37
- Force, measurement, 4.27-37
- 44, FET op amp, H.38
- 45, FET op amp, H.38
- 48, FET op amp, H.38
- Fourier analysis, 5.14
- Fourier transform, 5.17
- Fraden, Jacob, 4.37
- Franco, S., 5.133
- Franco, Sergio, 1.20, 1.93, 1.127
- Frantz, Rich, H.69

- Frederiksen, Thomas, H.49, H.67
 Frederiksen, Thomas M., 1.93
 Freeman, Wes, 7.75, 7.99
 Frequency dependent negative resistance filter, design, 5.66, 5.117
 Frequency domain, 5.1
 Frequency response, op amp, 1.69-74
 Frequency shaping stage, macromodel gain stage, 7.143
 Frequency transformation, filters, 5.51-58
 Friend, J.J., 5.133
 Frost, Seymour, H.17, H.26
 Fullagar, Dave, H.48, H.49, H.67, H.69
- G**
- Gain error, in-amp specification, 2.17
 Gain sense, in PGA, 2.38
 Gain-bandwidth product:
 op amp, 1.72-73
 voltage feedback op amp, plot, 1.73
 Gain-booster input composite amplifier, 6.197-205
 Galvanic isolation, driver, by transformer, 6.29
 GAP/R, H.20-21
 op amp firm, H.31-32, H.34-35
 GAP/R K2-P, H.20-21
 GAP/R model P2 varactor bridge op amp, H.33-34
 GAP/R model P45 solid-state op amp, H.32
 GAP/R model P65 solid-state op amp, schematic, H.31
 GAP/R model PP65 potted module solid-state op amp, H.33
 Garcia, A., 2.29, 6.10, 6.47, 6.77
 Garcia, Adolfo, 7.99, 7.137, 7.164
 Gaussian filter, 5.22
 design tables, 5.48-49
 response curves, 5.37-38
 Gaussian noise, 3.11
 Geffe, P.R., 5.133
 General capacitor information resource, 7.22
 General impedance converter, design, 5.64
 Gerke, Daryl, 7.137
 Germanium semiconductor, H.29
 Germano, Antonio, 7.163
 Gerstenhaber, Moshe, H.57, 6.187, 6.207
 Gianino, Mike, 6.187
 Gilbert, Barrie, 6.161
 Ginzton, Edward L., H.5, H.7, H.17, H.26, 1.29
 Goldberg, E.A., H.26
 Goldberg, Edwin A., H.17
 Goldberg, Harold, H.11, H.23
 Goodenough, Frank, H.66, H.71, 7.73
 Gosser, Roy, 1.127
 Gosser, Royal A., 1.29, 6.91
 Graeme, Jerald G., 4.67
 Grant, Doug, H.68, 7.22, 7.23, 7.50
- Graphics display system, video formats, 6.96-97
 Graphics resolution, versus pixel rates, non-interlaced refresh rate, table, 6.97
 Gray, Paul R., 1.93
 Gregg, Christopher, 7.137
 Ground:
 analog, 7.31-33
 concepts, 7.32
 currents, in precision amplifier, circuit, 7.38
 digital, 7.31-33
 isolation techniques, 7.38-40
 star, 7.31
 Ground loop, 7.29-31
 diagram, 7.30
 Ground noise, 7.29-31
 Ground plane, 7.33-34, 7.131-132
 breaks, 7.37
 key points, 7.34
 Ground reference, op amp, 1.32
 Grounded-input histogram, effect of ADC input-referred noise, 3.11
 Grounding, with "inverter-follower"
 differential line driver, 6.66
 Group delay, filter, curves, 5.28-38
 Grown junction silicon transistor, H.29
 Grundfest, Harry, H.12, H.24
 Guarding:
 inverting mode, 7.41
 MINIDIP (N) package, 7.43-44
 non-inverting mode, 7.42
 PCBs, 7.41
 SOIC surface mount "R" package, 7.44
 Guinta, Steve, H.43
- H**
- HA2500, H.66
 Hageman, E.C., H.25
 Hageman, Steve, 7.73
 Handbook of Chemistry and Physics, 4.91
 Hard limiter, ADC, 3.19
 Hardware, 7.1-164
 Harmonic distortion, 1.88, 3.14, 3.17-18
 ADC, location, 3.17
 Harrington, Brian, 6.187
 Harris Semiconductor, H.66
 Harris, E.J., H.12, H.24
 Hayes, John, 7.163
 Heat sink, 7.103-107
 definition, 7.103
 Henderson, K.W., 5.133
 Hendricks, Paul, 6.187
 Henning, H.H., 1.29
 Henry Ott Website, 7.138
 Higgins, H.C., H.24
 High impedance sensor, 4.39-67, 4.62-63
 High speed clamping amplifier, 6.120-123

■ OP AMP APPLICATIONS

- High speed current-to-voltage converter, inverting input capacitance effects, 1.120-124
- High speed op amp:
 - DC characteristics, 1.125-126
 - noise summary, 1.125
 - offset error summary, 1.126
- High voltage boosted output driver, 6.195-196
- High voltage boosted rail-rail composite op amp, circuit, 6.195
- High-Performance Dual FET Op Amps, H.69
- High-Performance Electrometer Op Amp in Plastic 8-Pin DIP, H.70
- High-speed video multiplexing, 6.124-126
- Highest-Performing Low-Cost BiFET Op Amps, H.69
- Highpass filter, 5.2, 5.8
 - distortion, 5.109
 - from Sallen-Key, transformation, 5.120
 - peaking versus quality factor, plot, 5.8
 - response, 5.14-16, 5.121
 - second-order response, 5.13
 - transfer function, 5.8
- Hilton, Barry, 1.29
- Hindi, David, 7.163
- Hoerni, Jean, H.30
- Hoerni, Jean A., H.41
- Hofer, Bruce, 6.47, 6.77
- Hogan, Steve, 6.10
- Hohman, Bruce, H.71
- Hold-to-sample mode transition, 3.31
- Holst, Per, H.13
- Holst, Per A., H.24
- Horizontal sync, 6.94
- Horn, Geoffrey, H.6
- HOS-050 high speed FET hybrid op amp, schematic, H.39-40
- HOS-100, open-loop bipolar hybrid amplifier, 6.79
- Howland circuit, 6.164
- Howland type current source, 2.27
- HP5082-4204 PIN Photodiode, characteristics, 4.59
- Huelsman, L.P., 5.133
- Human Body Model, for ESD, 7.95, 7.97
- Humidity monitor, 4.39
- Hunt, W., 5.134
- Husky, Harry, H.22, H.27
- Hybrid ground, cables, 7.120
- Hybrid op amp, H.30
- Hydrophone, 4.62, 4.65
 - piezo-ceramic cylinder, 4.65
- 7.93
- IC op amp, H.30
- ICL8007, monolithic P-channel FET input op amp, H.61
- IEC 1000-4-2, ESD test method, 7.95, 7.97
- IEC standards, for ESC testing, 7.95
- IEC testing, coupling methods, 7.96
- IEC, "Publication 98 (1964), Amendment no. 4," 6.27
- IEEE EMC Website, 7.138
- IEEE Standard for Performance Measurements of A/D and D/A Converters for PCM Television circuits, 6.137
- Impedance range, transformer, 6.6
- Impedance scaling factor, 5.114
- Improvements in or Relating to Arrangements for Amplifying Electrical Oscillations, H.6
- Impulse function, filter, definition, 5.17
- Impulse response, filter, curves, 5.28-38
- In-amp, 2.1-30
 - with 290MHz gain-bandwidth, 6.181
 - advantages, 2.8
 - applications, 2.25-30
 - A/D interface, 2.26
 - bridge amplifier, 2.25
 - driven current source, 2.26-27
 - remote load driver, 2.28
 - bridge amplification, 4.14
 - CMR, 2.2, 2.18
 - common-mode signal, 2.2
 - configuration, 2.1, 2.7-16
 - AD623 in-amp, 2.16
 - AD627 single-supply two op amp in-amp, 2.10-11
 - precision single-supply composite in-amp, 2.13-15
 - three op amp in-amp, 2.11-13
 - two op amp in-amps, 2.7-9
 - cross-coupled, for increased CMR, 6.186
- DC error, 2.17-20
 - bridge amplifier error budget
 - analysis, 2.22
 - gain, 2.17
 - noise specifications, 2.17
 - referred to input, 2.20
- definitions, 2.2
- gain, 2.2
- generic, circuit diagram, 2.2
- high CM voltage, CM over-voltage protection, 7.81-82
- input, and RFI rectification, 7.127-129
- input bias currents, 2.18
- input offset voltage, 2.18
- input overvoltage, 2.24
- noise model, 2.20
- noise sources, 2.20-23
 - input voltage, 2.20-21

- offset voltage model, 2.18
 - output offset voltage, 2.18
 - output voltage, 2.2
 - over-voltage protection, 7.87-90
 - performance, tables, 2.22-23
 - precision
 - data, 2.23
 - remote load driver, circuit, 2.28
 - precision bridge amplifier, circuit, 2.25
 - precision signal conditioning element, 2.25
 - precision single-supply composite, 2.13-15
 - RFI rectification, sensitivity tests, 7.122-123
 - single-supply
 - data, 2.23
 - over-voltage protection, 7.89
 - three op amp, circuit, 2.11-12
 - total noise, calculation, 2.21
 - total output noise, calculation, 2.21
 - versus op amp, 2.1
 - wideband, 6.184
 - In-circuit over-voltage:
 - protection, 7.91-95
 - op amp, 7.75-77
 - Individual resistor tolerance, in line receiver, 6.33
 - Inductance, 7.2, 7.16-21
 - equivalent series, 7.2
 - mutual, 7.16-18
 - signal trace routing, 7.17
 - stray, 7.16
 - Inductive coupling, 7.17
 - reduction via signal routing, 7.18
 - signal cabling, 7.18
 - Inductor:
 - filter problem, 5.101-105
 - parasitic effects, 7.19-20
 - Q or quality factor, 7.20
 - tuned circuits, 7.20
 - Infinite ground conductivity, 7.29
 - Input bias current, 1.58-61, 4.48
 - calculating total output offset error, 1.61
 - canceling effects (external to op amp), 1.60
 - in-amp, 2.18
 - op amp
 - diagram, 1.58
 - measurement, circuit, 1.59
 - Input bias current cancellation, H.53
 - Input capacitance, compensation, in current-to-voltage converter using VFB op amp, 1.121
 - Input capacitance modulation:
 - filter distortion, 5.107-112
 - compensation, plot, 5.108
 - Input current noise, 6.150
 - summary, 1.77
 - Input impedance, 1.62
 - current feedback op amp, diagram, 1.62
 - Input offset current, calculation, 1.59-60
 - Input offset voltage, 1.53-58
 - adjustments, 1.56-57
 - drift and aging effects, 1.58
 - in-amp, 2.18
 - op amp
 - diagram and specifications, 1.53
 - measurement
 - diagram, 1.54
 - using in-amp, circuit, 1.55
 - Input overvoltage, 1.43
 - Input pin isolation, 4.47
 - Input voltage noise, 4.53-56, 6.150
 - Johnson noise, 4.54
 - Instrumentation amplifier, see In-amp
 - Insulation resistance, 7.2
 - Integral linearity error, 3.9
 - Integrated circuit:
 - invention, H.29
 - planar process, invention, H.29
 - Integrated video multiplexers and crosspoint switches, 6.127-129
 - Integrator:
 - design, 5.63
 - digitally variable, circuit diagram, 5.130
 - Intensity, color, 6.96
 - Interconnection stability, resistors, 7.10
 - Interference, as unwanted information, 2.43
 - Intermodulation distortion:
 - communications amplifier, 6.140
 - plot, 6.141
 - third order intercept point, 6.141
 - plots, 6.142
 - Intersil, H.61
 - Inverter-follower differential driver, 6.65-66, 6.109-110
 - THD+N versus frequency, plots, 6.66
 - Inverting input, summing point, 1.7
 - Inverting op amp:
 - external offset trim methods, circuit, 1.57
 - protection, 7.82-83
 - Isolation amplifier, 2.43-51
 - applications, 2.43-44
 - carrier-operated, 2.46
 - input circuit, 2.44
 - linearity and isolation voltage, 2.44
 - Isolation barrier, 2.43
- J**
- Jenkins, Andrew, 6.207
 - Jensen JT-11P-1, transformer, 6.44-45

■ OP AMP APPLICATIONS

Jensen JT-OLI-2 isolation device, 6.69
Jensen Transformers, 6.44, 6.69
Jensen, Deane, 6.47, 6.77
JFET, rectification sensitivity, versus BJT, 7.125
JFET input op amp:
 headroom needs, 1.39
 output phase-reversal, 7.83-84, 7.90
 PNP or N-channel stages, with CM inputs, diagrams, 1.40
 showing offset and drift trims, diagram, 1.39
Jofeh, Lionel, H.11, H.23
Johnson noise, 1.76, 1.78, 1.84, 1.86, 3.7, 4.52-53, 6.149, 6.165, 7.82
 broadband, 4.53
 resistor, 4.54, 7.13
 spectral density, 4.53
Johnston, Denis L., H.11, H.24
Jones, Morgan, H.27
JT-11-DM, 6.69
JT-11P-1 Line Input Transformer Data Sheet, 6.47
JT-OLI-2, 6.69
Julie, Loebe, H.16-17
Jung, W., 5.134, 6.10, 6.27
Jung, Walt, H.1, H.68, H.70, 1.1, 1.3, 1.23, 1.31, 1.53, 1.95, 2.1, 2.29, 3.46, 4.1, 4.69, 6.1, 6.10, 6.27, 6.47, 6.77, 6.79, 6.91, 6.137, 6.163, 6.187, 6.189, 7.1, 7.51, 7.73, 7.75, 7.101, 7.108, 7.109, 7.137, 7.139
Jung, Walter G., 1.20, 1.93, 6.10, 6.207, 7.22

K

K2-W op amp, H.20-21
Kaufman, M., 1.93, 6.27
Kautz, W.H., 5.133
Kelvin connections, for RTD, 4.80
Kelvin feedback, 7.27-28
Kelvin sensing, 4.20-21, 4.31, 4.34
 ratiometric reference, diagram, 4.24
Kester, W.A., 6.137
Kester, Walt, H.43, 1.1, 1.20, 1.23, 1.31, 1.51, 1.53, 1.93, 1.95, 1.102, 1.103, 1.127, 2.1, 2.31, 2.43, 3.5, 3.20, 3.41, 3.46, 3.53, 4.1, 4.5, 4.7, 4.25, 4.27, 4.37, 4.39, 4.67, 4.69, 4.91, 6.1, 6.79, 6.91, 6.93, 6.137, 6.139, 6.163, 7.1, 7.51, 7.73, 7.75, 7.99, 7.108, 7.109, 7.137, 7.139
Key, E.L., 5.133
Kilby, Jack, H.29-30
Kilby, J.S., H.41
Kimmel Gerke Associates Website, 7.138
Kimmel, William, 7.137
King, Grayson, 4.5

Index 20

Kirchoff's laws, 5.5, 7.16, 7.28
Kitchin, Chuck, 2.29, 4.1, 4.39, 7.99, 7.137
Kline, Barry, 6.207
Konigsberg, R.L., H.22, H.27
Koren, Victor, 6.187
Korn, G., 6.27
Korn, Granino, H.18-19, H.22, H.26, H.27
Korn, T., 6.27
Korn, Theresa, H.18-19, H.26, H.27
Krehbiel, John, 2.41
Kress, Dave, H.66, H.69, H.71
Kurz, Dov, 7.99

L

Lapham, Jerome F., H.70
Lapham, Jody, H.65
Laplace transform, 5.1, 5.17
 in RIAA response, PSpice circuit analysis, 6.20, 6.23
Laser trimming:
 advantages, 1.49
 for precision amplifiers, 1.48
Law of Intermediate Metals, 4.72
Leaded ferrite bead, 7.68
Leakage, 7.2
 circuit board static effect, 7.40
 surface, eliminating, 7.41
Least significant bit, see LSB
Leclercq, Paul De Raymond, H.27
Lee, P., H.51, H.67
Lee, Seri, 7.108
LF155, H.61, H.63
LF156, H.61, H.63
LF157, H.61, H.63
LH0033, open-loop FET input hybrid amplifier, 6.79
LH101, monolithic IC op amp, hybrid topology, H.49
Lightning Empiricist, periodical, H.21
Line driver:
 audio, 6.48-64
 composite current boosted, 6.62-64
 circuits, 6.62-64
 current boosted buffered, 6.60-61
 circuit, 6.60
 THD+N versus frequency, plots, 6.61
differential, 6.65-68
fixed-gain video transmission, 6.82
high efficiency, 6.163-164
mixed feedback, 6.71
paralleled output, 6.57
single-ended, 6.55-64
 mixed feedback transformer, circuit, 6.72
transformer coupled, 6.69-76
 basic, 6.69-70
 circuit, 6.69
 feedback, 6.71-76

- video, high efficiency, circuit, 6.163
- wide dynamic range ultra low distortion, 6.58-59
- xDSL upstream, 6.158-160
- Line input transformer, audio signals, CM isolation, 6.44-45
- Line receiver:
 - balanced, 6.36
 - buffered input, 6.40-41
 - CM error versus frequency, plots, 6.42-43
 - diagram, 6.40
 - performance, 6.41-43
 - CM error versus frequency, plot, 6.38
 - TD+N, 6.39
 - buffered balanced, advantages, 6.47
 - CM rejection versus frequency, plot, 6.34
 - differential, balanced feedback, 6.36
 - summary, 6.47
 - transformer-input, 6.44-46
 - advantages, 6.47
 - circuit, 6.44
 - CMR errors, plot, 6.45
- Linear Design Seminar (1995), 2.41, 2.51
- Linear IC pioneer, H.72
- Linear IC regulation, 7.52
- Linear phase with equiripple error, response curves, 5.35-36
- Linear post regulator, supply switching, 7.63
- Linear regulator, op amp power supply, 7.51
- Linear Technology Corporation, H.53
- Linear voltage regulator, basics, 7.52-54
- Link trimming, 1.48
 - advantages, 1.49
- Lipshitz, S., 6.27
- LM101:
 - monolithic IC op amp
 - design objectives, H.46
 - schematic, H.47
 - second generation, H.46-48
 - two-stage topology, H.46
- LM101A, monolithic IC op amp, greater stability, H.49
- LM102, voltage follower, H.51
- LM107, monolithic IC op amp, H.49
- LM108, H.55
 - super-beta input monolithic IC op amp, H.52
 - schematic, H.52
- LM108A, super-beta input monolithic IC op amp, H.52
- LM110, voltage follower, H.51
- LM112, super-beta input monolithic IC op amp, H.52
- LM118, H.66
- LM148, quad IC op amp, H.49
- LM281, H.66
- LM317, adjustable voltage regulator, 7.54-55
- LM318, H.66
- LM324, quad op amp, industry standard, H.49
- LM358, dual op amp, H.49
- Load cell, 4.27
 - amplifier circuit, with Kelvin sensing, 4.34
 - single-supply amplifier, diagram, 4.35
 - using strain gages, diagram, 4.31
- Long-tailed pair, H.10, 1.104
- Longrie, Gary, H.7, H.27
- Loop gain, with frequency, filter, 5.109
- Loops, ground network, 7.30
- Loophrough amplifier, 6.119
- Lorber, Matt, H.35
- Losmandy, Bela, H.22, H.27
- Lovell, C.A., H.13, H.25
- Low Dropout regulator, 7.52
 - architectures, 7.55-59
 - pole splitting, 7.56
 - see also LDO
- Low noise charge amplifier, circuit configurations, 4.63-64
- Low noise PGA, using AD797 and ADG412, circuit, 2.35
- Low-Cost HOS-050C Is Internally Compensated,
 - Settles to 0.1% in 80ns, 0.01% in 200ns, H.43
- Low-noise JFET gain-boosted input composite amplifier, 6.204-205
- Low-Noise, Low-Drift Precision Op Amps for Instrumentation, H.70
- Lowpass filter, 3.32, 3.45, 5.2, 5.26-49
 - from Sallen-Key, transformation, 5.119
 - peaking versus quality factor, plot, 5.7
 - phase response, 5.14-16
 - prototype, 5.8
 - response, 5.121
 - second-order response, 5.13
 - to allpass, frequency transformation, 5.57-58
 - to bandpass, frequency transformation, 5.52-55
 - to bandreject, frequency transformation, 5.55-57
 - to highpass, frequency transformation, 5.51-52
 - to notch, frequency transformation, 5.55-57
 - using AD8048 voltage feedback op amp, 1.120
- LPKF Laser & Electronics, 7.164
- LSB, resolution of data converter, 3.7
- LT1008, super-beta op amp, H.53
- LT1012, super-beta op amp, H.53
- Luminance, 6.95
- Lundahl LL1517 transformer, 6.73-76

■ OP AMP APPLICATIONS

THD+N versus frequency, plots, 6.71
Lundahl LL1582 transformer, 6.72-74
 without Faraday shield, 6.73
Lundahl LL2811 transformer, 6.72
 THD+N versus frequency, plots, 6.73
Lundahl, Per, 6.77-78
Lyne, Niall, 7.99

M

M9 gun director, H.13
 designers, H.15
 Medal of Merit for designers, H.15
 with SCR584 radar system, H.15
M9 op amp, schematic, H.19
 μ A702, first monolithic IC op amp, H.45
The μ A702 Wideband Amplifier, H.67
 μ A709:
 monolithic IC op amp, H.45-46
 schematic, H.45, H.47
 μ A725, H.53, H.55-59
 monolithic IC op amp, schematic, H.55
 μ A740, H.61
 μ A741:
 monolithic IC op amp, H.48-49
 schematic, H.48
 similarity to AD741, H.50
 μ A748, externally compensated monolithic IC
 op amp, H.49
McCoy, R., 6.27
McCoy, Rawley, H.18, H.26
McFee, Richard, H.12, H.24
Machine Model, for ESD, 7.95
MacKenzie, Scott, 4.5
Macromodel:
 advantages and disadvantages, 7.140
 current feedback, 7.141, 7.147-148
 gain stage, frequency shaping, 7.143
 input stage, rail-rail, 7.145
 op amp, ADSpice model, 7.141
 output stage, 7.144-145
 general-purpose, circuit, 7.144
 transient response, 7.145
 versus micromodel, 7.140-141
 voltage feedback, 7.141
Magnetic phono cartridges, topology, 6.16
Maidique, Modesto, H.68, H.69
Maidique, Modesto "Mitch," H.54, H.60
Main amplifier, 1.98-100
Malter, Bob, H.31, H.34
Marcin, Joe, 4.91
Mark Montrose Website, 7.138
Mark, M., 7.22
Mark, W., 7.50
Marsh, R., 6.27
Marsh, Richard, 7.22
Marwin, Bob, H.71
MAT02 Low Noise, Matched Dual Monolithic
 Transistor Data Sheet, 6.207
MAT03 Low Noise, Matched Dual PNP
 Transistor Data Sheet, 6.207
Matrix board, prototyping system, 7.153
Matthews, B.H.C., H.9, H.23
May, Dale, H.69
MC1458, dual IC op amp, H.49
MC1556, super-beta op amp, H.51
MC1558, dual IC op amp, H.49
MC4741, quad IC op amp, H.49
MD3257, H.36
Melliard-Smith, C. Mark, H.41
Melsa, James L., 1.93, 1.127, 4.67
Mesa process, for IC development, H.30
MESC series RFI suppression chokes, 7.73
Metal foil strain gage, 4.29
Metal migration, op amp, 7.76
Meyer, Robert G., 1.93
Mezger, G. Robert, H.11, H.23
Mica capacitor, 5.103-104
Micro-Gee PProducts, Inc., H.22
MicroConverter Technology Backgrounder, 4.5
Micromodel:
 advantages and disadvantages, 7.140
 versus macromodel, 7.140-141
Microphone preamp:
 audio, 6.1-10
 electret interface, 6.4
 circuit, 6.4
 single-ended, single-supply high-
 impedance, 6.2-3
 transformer-coupled, THD+N, 6.7
 transformer-coupled low-impedance, 6.5-7
 circuit, 6.5
 very low noise transformer-coupled, 6.8-9
 circuit, 6.8
 THD+N, 6.9
Microphonics, in capacitors, 5.103
Microstrain, 4.27
Microstrip, 7.131-133
 delay constant, 7.133
 rules, 7.133
 transmission line, 7.36
MIL-PRF-55182G, 2.29
MIL-STD-883 Method 3015, 7.99
MIL-STD-883 Method 3015 classification, 7.95
MIL-STD-883B Method 3015.7 test method,
 7.96-97
Millaway, Steve, H.63, H.69
Miller circuit, 1.26
Miller Integrator, 1.109
Miller-compensated low drift system, H.17
Miller, Stewart, H.5, H.17
Miller, Stewart E., H.7, H.26, 1.29
Milne, Bob, H.7, H.27
Mindell, David, H.5, H.15
Mindell, David A., H.6, H.25-26
Mini-Mount, prototyping system, 7.155
MINIDIP (N) package, 7.43-44

- Minimum passband attenuation, filter, 5.3
 - Missing codes, excess DNL in ADCs, 3.10
 - Mixed feedback driver, 6.71
 - balanced transformer, circuit, 6.75
 - THD+N versus frequency, plots, 6.74
 - Mixed-Signal and DSP Design Techniques (2000), 2.51
 - MMDT2222A Dual NPN Small Signal Surface Mount Transistor Data Sheet, 6.207
 - MMDT2907A Dual PNP Small Signal Surface Mount Transistor Data Sheet, 6.207
 - Mode conversion, and CMR noise, 6.32
 - Model 3xx series varactor bridge op amps, H.35
 - Model 44 Fast Settling High Accuracy Op Amp Data Sheet, H.42
 - Model 45 Fast Settling FET Operational Amplifier Data Sheet, H.42
 - Model 48 Fast Settling Differential FET Op Amp Data Sheet, H.42
 - Model 50: Wideband, Fast Settling Op Amp, H.43
 - Model 50 Fast Settling 100mA Output Differential FET Op Amp Data Sheet, H.42
 - Model 310, 311 Ultra Low Bias Current Varactor Bridge Operational Amplifiers Data Sheet, H.42
 - Modular op amp, H.30
 - Moghim, Reza, H.71
 - Monolithic IC electrometer amplifier, H.63-64
 - Monolithic IC op amp, birth, H.45-51
 - Montrose, Mark, 7.137
 - Website, 7.138
 - Morrison, Ralph, 7.50, 7.137
 - MOSFET, 1.39, 6.170
 - in over-voltage protection, 7.80
 - Motchenbacher, C.D., 6.10, 7.99
 - Motor control isolation amplifier, 2.46
 - Motorola Semiconductor, H.49, H.51
 - Moving coil, in magnetic phono cartridges, 6.16
 - MPS6521, H.38
 - MPTR, plots, 6.143
 - Mu-metal, 7.113
 - Multi-tone intermodulation distortion, 3.14
 - Multiple feedback filter:
 - bandpass
 - design, 5.87
 - diagram, 5.110
 - design, 5.70-71, 5.116
 - distortion, 5.109
 - highpass, design equations, 5.86
 - lowpass, design equations, 5.85
 - op amp limitations, 5.107
 - transformation, 5.121
 - Multiplexed data, op amp considerations, 3.26-27
 - Multiplexer:
 - expansion, 6.129
 - fault-protected, 7.81
 - key specifications, 3.26
 - Multiplexing, definition, 3.26
 - Multitone power ratio, 6.143
 - Muncy, N., 6.47
 - Murphy, Mark, 6.187, 6.207
 - Murphy, Troy, 7.163
 - Mutual inductance, 7.16-18
 - magnetic fields, 7.18
- N**
- Nagel, L.W., 7.163
 - National Semiconductor Corporation, H.46, H.49, H.61, H.66
 - Negative feedback theory, filter, 5.106
 - Negative resistance buffer, 6.185
 - circuits, 6.185
 - Nelson, David A., 1.29
 - Neper frequency, 5.5-6
 - New Modular Op Amps, H.42
 - Newton, A.R., 7.163
 - Nexus Research Laboratories, H.33-35
 - Nobel Prize:
 - for IC, H.29-30
 - for transistor, H.29
 - Noble, Roger R. (Tim), H.33
 - Noise:
 - in audio line receiver, 6.30
 - calculation, op amps, 6.150
 - capacitance-coupled, reduction, 7.112
 - common-impedance
 - circuitry changes, 7.112
 - reducing, 7.110-111
 - solutions, summary, 7.111, 7.111
 - communications, 6.144-152
 - components, 6.148
 - coupling, mechanisms, 7.110-111
 - inductance, near-field interference, 7.112-113
 - magnetically-coupled
 - reduction, 7.113
 - methods, 7.113
 - model, 1.84
 - op amp circuit, calculation, 6.148
 - pole/zero cell impedance reduction, 7.146
 - popcorn, 1.80
 - referred to input, 1.84
 - RMS, 1.80-83, 6.148
 - RMS to peak-to-peak ratios, 1.83
 - source versus output, table, 6.149
 - sources
 - referred to output
 - second-order system, summary, 1.87
 - summary, 1.85
 - sources versus impedances, 1.78
 - total output, calculations, 1.83-87

■ OP AMP APPLICATIONS

- voltage, 6.149
 - Noise factor:
 - definition, 6.145
 - resistive, reactive, and unterminated conditions, definition, 6.146-147
 - Noise figure:
 - available power, 6.144
 - communications amplifier, 6.144
 - comparison at impedance level, 6.147
 - definition, 6.145
 - input termination, effect, 6.147
 - op amp, calculation, 6.146
 - Noise gain, 1.86
 - increase, follower or inverter stability, diagrams, 6.84
 - op amp, calculation, 1.118-119
 - second-order system, plot, 1.87
 - signal gain
 - manipulating, 1.63
 - op amp, manipulation, 1.63
 - voltage feedback op amp, Bode plot, 1.73
 - Noise generator, wide bandwidth, 6.165-166
 - Noise index, resistors, 7.14
 - Noise model, 7.145-147
 - Noise reduction:
 - linear post regulator for supply switching, 7.63
 - power supply, 7.64
 - switching, capacitors, 7.64-67
 - using output filtering, 4.55
 - Noise voltage, mode conversion, 6.32
 - Non-inverting input current noise, 4.54
 - Non-inverting op amp external offset trim methods, circuit, 1.57
 - Non-monotonicity, DAC, 3.9
 - Nonlinear phase, effect on filter, 5.16
 - Nonlinearity:
 - definition, 2.17
 - error, resistors, 7.10
 - "Nostalgia" vacuum tube input/output
 - composite op amp, 6.206
 - cascode stage, 6.206
 - circuit, 6.206
 - Notch filter, 5.2, 5.10-11
 - 60Hz, 5.131-132
 - schematic, 5.132
 - second-order response, 5.13
 - width versus frequency, plot, 5.11
 - Nova Devices, H.54
 - Noyce, Robert, H.29-30
 - Noyce, Robert N., H.41
 - NTSC:
 - color subcarrier frequency, 6.95
 - composite color video line, diagram, 6.94-95
 - video amplifier, headroom, 6.133
 - video distortion, 6.116
 - Null:
 - bridge, 4.9
 - measurement, 4.9
 - Nulling amplifier, 1.98-100
 - Nyquist bandwidth, 3.2, 3.10
 - Nyquist shift, H.11
 - Nyquist, Harry, H.5-7
 - Nyquist's criterion, H.5
- ## O
- Och, Henry, H.13
 - Off-channel isolation, multiplexer, 3.26
 - Offenberg, Arne, 6.78
 - Offner, Franklin, H.9, H.11, H.23-24
 - Offset adjustment:
 - external methods, 1.56-57
 - internal method, 1.56
 - pins, 1.56
 - Offset error:
 - bridge, 4.22
 - from CMRR, calculation, 1.89
 - Offset voltage trim processes, 1.47-49
 - Ohmite Victoreen MAXI-MOX Resistors, 4.67, 7.22
 - Ohm's law, 5.5, 7.27
 - OMEGA Temperature Measurement Handbook, 4.91
 - On-resistance, multiplexer, 3.26
 - 1/f noise, 1.79
 - 101:
 - monolithic IC op amp, second generation, H.46-48
 - pole splitting compensation, H.48
 - two-stage voltage amplifier topology, H.48
 - 121, wideband DC op amp, H.36-37
 - 180, low drift chopper-less op amp, H.36
 - 183, low drift chopper-less op amp, H.36
 - Op amp:
 - accuracy, and filter performance, 5.117
 - as ADC driver, 3.21
 - requirements, 3.21
 - ADSpice model, open-loop gain versus frequency, 7.142
 - basics, 1.1-128
 - bias current, 1.4
 - BiCMOS, 1.96
 - BiFET, 1.96, 1.103
 - output voltage phase-reversal, 7.83-84
 - bipolar, 1.96
 - bias current compensation, 1.35
 - uncompensated bias current, 1.35
 - versus chopper stabilized, 1.101
 - voltage noise, 1.77
 - bipolar transistor, H.35
 - breakdown, over-voltage, 7.76
 - capacitive loading, stability, 6.84
 - categories, H.36
 - CB, 1.103

- channel protector, 7.80
 - advantages, 7.80
- chopper stabilized, 1.54, 1.98-100
 - basic circuit, 1.98
 - diagram, 1.99
 - intermodulation, spectra, 1.99
 - lowest offset and drift performance, 1.98
 - noise, 1.101
 - voltage noise spectral density, spectra, 1.100
- chopper-stabilized, H.17-18, H.36
 - advantages, H.18
 - limitations, H.18
- circuit noise, calculation, 6.148
- closed loop feedback, 1.5
- closed loop gain, 1.4
- CM over-voltage protection circuit, 7.76
- CMOS, 1.96
- CMRR, power supply rejection ratio (PSRR), 89-92
- common mode dynamic range, 1.15-17
 - input dynamic range, 1.16-17
 - output dynamic range, 1.15-16
 - single-supply system, 1.16
- common mode over-voltage protection, using CMOS channel protectors, 7.80-82
- common mode rejection, 1.4
- comparisons between voltage feedback and current feedback, 1.124-125
- complementary bipolar, 1.96
- composite, high voltage boosted rail-rail, circuit, 6.195
- current feedback, 1.1, 1.23, 1.113-117
 - closed-loop bandwidth, 1.115
 - current-on-demand, 1.114, 1.116
 - in current-to-voltage converter, 1.122
 - diagram, 1.23
 - error current, 1.114
 - important features, 1.117
 - input capacitance sensitivity, 1.123
 - low inverting input impedance, 1.123
 - model and Bode plot, 1.114
 - no slew-rate limitation, 1.114
 - noise calculation, 6.150
 - performance summary, 1.117
 - simplified diagram, 1.113
 - simplified two-stage, diagram, 1.116
 - solid state, Bell Labs, diagram, 1.28
 - summary of characteristics, 1.117
- current feedback model, 7.147-148
- data conversion, 3.1
 - applications, 3.2
 - characteristics, 3.3-4
- DC coupling, 3.33-34
- decompensated, 1.72
- decoupling, techniques, 1.92
- design points, 7.105-106
- developments, H.13-16
- device/topology distortions, 6.52-55
- differential amplifier, 1.9
- differential input, 1.4
- diode leakage, protection network, 7.78
- distortion, 1.88
- drift problem, H.17
- dual triode front end, H.20
- dual-supply, 1.17-18
- dynamic range, definitions, 1.88
- dynamics, and filter performance, 5.118
- electrometer IC, H.63-64
- evaluation boards, 7.160-162
 - dedicated, 7.161-162
- external feedback elements, 1.3
- feedback capacitance
 - effects, 1.118-120
 - noise gain stability analysis, 1.118
- FET technology, H.35
- FET-input, RFI susceptibility, 7.122-123
- FET-output, phase-reversal, summary, 7.85
- as filter, 1.119-120
- frequency response, 1.68-75
 - on filter quality, 5.110-111
 - settling time, 1.69-72
 - slew rate and full-power bandwidth, 1.68-69
- fully differential design, schematic, H.22
- gain setting and level shifting, 3.33-34
 - circuits, 3.33
- general circuit, feedback, 1.5
- general introduction, H.3-8
- general-purpose, DC-coupled, high gain, inverting feedback amplifier, H.2
- ground reference, 1.32
- harmonic distortion, 1.88
- heat sink, 7.103
 - using TO99 metal can type, 7.103
- high gain, H.2
- high speed, 1.103-127
 - amplifier bandwidth versus supply current, plots, 1.103
 - DC characteristics, 1.125-126
 - noise summary, 1.125
 - offset error summary, 1.126
- high speed FET, family, H.37-40
- high speed IC, H.66
- historical background, H.1-2
- history, H.1-72
- hybrid, H.29-44, H.30
 - designs, H.31-40
- IC, H.30, H.45-72, H.62
 - monolithic, birth, H.45-51
- ideal, attributes, 1.3-5
- in-circuit over-voltage, protection, 7.75-77
- in-circuit voltage, 7.75

■ OP AMP APPLICATIONS

- input common mode limits, 7.75-77
- input differential protection, 7.86-87
- input and output voltage dynamic ranges, 1.18
- input overvoltage, 1.43
- input and RFI rectification, 7.126-127
- input stages, 1.34-43
 - bias current compensated bipolar, 1.36-37
 - bias current compensated super-beta bipolar, 1.38
 - bipolar, 1.34-35
 - FET, 1.38-39
 - overvoltage considerations, 1.43
 - rail-rail, 1.40-43
- integrated circuit, H.45-72
- inverter, 1.8
- inverting
 - external offset trim methods, circuit, 1.57
 - and noninverting, guard techniques, 4.45
 - protection, 7.82-83
 - summer, 1.9
- inverting mode operation, H.2
- JFET
 - output phase-reversal, 7.90
 - output voltage phase-reversal, 7.83-84
- JFET IC, H.65
- Karl Swartzel, H.14-15
- limitations in filters, 5.106-107
- load immunity, 1.18
- long-term stability, 1.58
- low noise, filtering, noise performance, 3.45
- low noise JFET IC, H.65
- low source impedance, 1.4
- low-drift, high gain, H.20-21
- low-leakage input clamping, 7.78
- macromodel
 - accuracy checking, 7.149
 - current feedback, input and gain stages, 7.147
- metal migration, 7.76
- model 3xx series varactor bridge, H.35
- modern IC packages, scale, H.59
- modular, H.30
 - designs, H.31-40
- multiplexed data acquisition, applications, 3.26-27
- multistage, 1.26
- naming, H.16
 - by Ragazinni, 1.3
- noise, 1.76-87
 - components, 6.148
 - frequency characteristic, diagram, 1.79
 - popcorn noise, 1.80
 - RMS noise, 1.80-83
 - total noise calculations, 1.83-87
- noise figure, 1.79
- noise gain and signal gain, manipulation, 1.63
- noise model, 1.84
 - first-order circuit, 3.12
 - RTI and RTO noise, 3.12
 - second-order system, 1.85-86
- non-IC solid state, H.1
- non-ideal
 - circuit, 1.10
 - error multiplier, 1.11
 - gain stability, 1.12
 - loop gain, 1.12-13
 - frequency dependence, 1.13-15
 - plots, 1.13
 - noise gain, 1.11-12
 - signal gain, 1.11
 - static errors from finite amplifier gain, 1.10-15
 - voltage feedback, 1.14
- non-inverting, external offset trim methods, circuit, 1.57
- non-inverting input, H.19-20
- normal signals, 7.75
- offset voltage, 1.4
- open-loop gain, 1.4
- out-of-circuit voltage, 7.75
- output noise, calculation, 3.12-13
- output stages, 1.44-49
 - offset voltage trim processes, 1.47-49
 - surge protection, 1.46
- output voltage phase-reversal, 7.83-84
- over-voltage protection, clamping diode leakage, 7.77-78
- overall loop feedback, H.3
- packaging, H.59
- passive components, 7.1-24
- performance, JFET versus bipolar, 4.65-66
- power supply
 - conditioning techniques, summary, 7.72
 - and decoupling, 1.92
 - and power dissipation, 1.92
 - regulation, 7.51
 - systems, 7.51-74
- precision, 1.18, 1.95-102
 - characteristics, 1.96
 - DC error budget analysis, 1.96-97
 - open-loop gain, 1.95
 - resolution error, 1.96-97
 - selection, 1.95
 - single-supply, performance characteristics, compared to OP177F, 1.97
- precision bipolar IC, H.55-59
- precision JFET IC, H.60-66
- process technologies, 1.50

- protection, 7.75-100
- quiescent current, and biasing, 6.195
- reverse junction breakdown, 7.86
- RFI rectification, sensitivity tests, 7.122-123
- sampled data system, diagram, 3.1
- selection criteria, for data converters, 3.4
- selection drivers, table, 1.19
- settling time, 3.27
- signal conditioning, 3.1
- single-ended to differential conversion, circuit, 3.37
- single-supply, 1.17-18, 1.31-33
 - design issues, summary, 1.33
 - gain accuracy, 1.31
 - guarding, 7.44
 - input stage, characteristics, 1.32-33
- solid state
 - schematic, H.31
 - varactor bridge, H.33-34
- solid-state modular, H.29-44
- and source impedances, plots, 1.78
- specifications, 1.53-93
 - for ADC applications, 3.22-24
- SS bipolar, output phase-reversal, 7.90
- standard feedback circuits, 1.6-10
 - differential stage, 1.9-10
 - inverting stage, 1.8-9
 - non-inverting stage, 1.6-7
- standard value resistors, and filter performance, 5.118
- structures, 1.31-51
- subtractor, 1.9
- summing amplifier, 1.9
- summing point, 1.8
- super-beta IC, H.51-54
- super-beta input stage transistors, bias current compensation, circuit, 1.38
- supply voltage limitations, 1.18
- THD+N, 1.88
- THD, 1.88
- thermal considerations, 7.101-108
- thermal management, 7.101-108
- thermal rating curves, 7.103
- thermal relationships, chart, 7.102
- thermal resistance, 7.101
- topologies, 1.23-29
- total dynamic range, 1.18
- total offset voltage, model, 1.61
- traditional output stages, diagrams, 1.44
- two signal inputs, H.17
- two-chip hybrid IC, bias current specification, H.61
- two-tube design, H.16
- unity gain inverter, 1.9
- use, with data converters, 3.31-54
- vacuum tube, H.9-28
 - chopper stabilized, H.17-19
 - declining years, H.22
 - evolution, H.17-22
- varactor bridge design, H.63
- versus in-amp, 2.1
- video driver, power dissipation, graph, 7.106
- virtual ground, 1.8
- voltage and current output, 1.18
- voltage feedback, 1.1, 1.23, 1.104-112
 - all NPN process, circuit, 1.105
 - bandwidth and slew rate calculations, 1.108
 - closed-loop relationship, 1.106-107
 - complementary bipolar design, 1.109-111
 - in current-to-voltage converter, and input capacitance, 1.121
- device families, 6.106
- diagram, 1.23
- folded cascode, 1.110
- full-power bandwidth, 1.107-108
- high speed, table, 1.112
- long-tailed pair, 1.104
- model and Bode plot, 1.106
- noise calculation, 6.150
- "Quad-Core" stage, diagram, 1.111
- slew rate, 1.107
- two gain stages, diagram, 1.109
- two stage, model, 1.109
- unity gain-bandwidth frequency, 1.106
- voltage follower, 1.6
- XFCB, 1.104
- Op amp integrator, versus grounded capacitor integrator, plots, 6.180
- Op amp noise, 1.76-87
 - input voltage, circuit, 1.76
- Op Amp Settles to 0.01% in 300 ns, H.42
- Op Amps Combine Superb DC Precision and Fast Settling, H.70, 1.29
- OP07:
 - monolithic IC op amp
 - schematic, H.57
 - single-supply and micro-packaged compatibles, H.59
 - ultralow offset voltage bipolar op amp, 4.42
- OP27:
 - bias compensated op amp, 1.36-37
 - bipolar op amp, 4.65
 - low noise op amp, 7.86
 - monolithic IC op amp, schematic, H.59
 - multiple stage, pole-zero compensated amplifier, 6.166
- OP37, monolithic IC op amp, schematic, H.59
- OP42, FET input op amp, for high speed photodiode preamps, 4.59
- OP90:

■ OP AMP APPLICATIONS

- Bode plot, 5.111
- DC precision amplifier, 5.110
- OP97:
 - composite op amp, gain versus frequency, plots, 6.194
 - super-beta bipolar op amp, 1.35, 1.38, 4.42
- OP97/297/497, super-beta input monolithic IC op amp, schematic, H.53
- OP113, low-drift low-noise amplifier, 2.37
- OP177:
 - CMR, plot, 1.89
 - gain nonlinearity, plots, 1.67
 - input voltage noise, plot, 1.81
 - power supply rejection, 1.91
 - precision bipolar op amp, 1.101, 4.22, 4.33
- OP177F, precision op amp, DC error budget analysis, table, 1.97
- OP213:
 - dual precision op amp, in bridge circuit, 4.16
 - peak-to-peak noise, spectrum, 1.81
- OP275, 2.6
 - bipolar/JFET input op amp, 3.52, 6.53-54, 6.65
 - THD+N versus frequency, plots, 6.53-54
 - inverter, 6.38-39
 - microphone preamplifier, 6.7
- OP284, true rail-rail input op amp, schematic, 1.43
- OP297:
 - dual op amp, H.54
 - high performance super-beta bipolar op amp, 1.35, 1.38
- OP497:
 - high performance super-beta bipolar op amp, 1.35, 1.38
 - quad op amp, H.54
- OP727, dual op amp, H.59
- OP747, quad op amp, H.59
- OP777:
 - precision bipolar op amp, 4.76
 - precision op amp buffer, 7.80
 - single op amp, H.59
- OP777/OP727/OP747 Precision Micropower Single-Supply Operational Amplifiers Data Sheet, 1.102
- OP1177:
 - precision amplifier, 4.22
 - single op amp, H.59
- OP1177/OP2177/OP4177 Precision Low Noise, Low Input Bias Current Operational Amplifiers Data Sheet, 1.102
- OP2177:
 - dual op amp, H.59
 - dual precision op amp, in bridge circuit, 4.16
- OP4177, quad op amp, H.59
- OPA111, monolithic IC electrometer amplifier, H.63
- Opamp Labs Inc., H.27
- Open-loop gain, 1.64
 - measurement, circuit, 1.66
 - nonlinearity, 1.64-67
 - calculation, 1.67
- Operational amplifier, named by Ragazzini, H.16
- Optimum turns ratio, transformer, calculation, 6.6
- Optional noise reduction post filter, 2.46
- Optocoupler, 2.48
- Optoelectronics Data Book, 4.67
- Optoisolator, 2.43, 2.48
- Order, filter, 5.3
- OS-CON Aluminum Electrolytic Capacitor Technical Book, 7.73
- Oscon capacitor, 6.73
- Ott, Henry, 6.47, 7.137
 - Website, 7.138
- Ott, Henry W., 7.23, 7.50, 7.73
- Out-of-band SFDR, 6.143
- Output compliance voltage, 3.48
- Output impedance, in FDNR filter, 5.107
- Output offset voltage, in-amp, 2.18
- Output stage surge protection, 1.46
- Output voltage phase-reversal, 7.83-84
 - fixes, 7.85-87
 - test procedure, 7.84
- Overvoltage, 3.40
 - in-circuit points, summary, 7.90
 - in-circuit protection, 7.90-95
 - protection for in-amp input, 2.24

P

- PADS Software, 7.164
- PAL, color subcarrier frequency, 6.95
- "Palimpsest," H.21
- Pallas-Areny, Ramon, 4.25, 4.37, 4.67, 4.91
- Palmer, Wyn, H.66, 1.29
- Paralleled amplifiers:
 - quiet load driving, 6.168-169
 - circuits, 6.168
- Paralleled output line driver, 6.57
 - dual op amp, circuit, 6.57
 - THD+N versus frequency, plots, 6.57
- Parasitic capacitance, 7.10-11
- Parasitic inductance, 7.10-11
- Parasitic leakage, reduction, 4.45
- Parasitic pole, 6.84
- Parasitic thermocouple, 4.22, 7.11
- Parasitic thermocouple effects, 1.100
- Parasitics, 5.103, 7.150-151
 - and pin sockets, 7.158
 - resistor, 7.10-11
- Parkinson, David, H.13

- Parks, Steve, H.71
- Parnum, D.H., H.11-12, H.24
- Pass device, 7.54
 inverting mode, 7.54
- Passband filter, 5.2
- Passband ripple, filter, 5.3
- Passive capacitance, 5.103
- Passive component:
 analysis, 7.21
 and EMI, 7.114-115
 filter problems, 5.101-105
- Passive filter:
 design, 5.115
 normalized, 5.114
- Passive LC section, design, 5.60-63
- Passively equalized RIAA preamp:
 optimization, 6.25
 topology, 6.24-26
 circuit, 6.24
- Patterson, Omar, H.20
- Patterson, Omar L., H.27
- Paynter, Henry, H.27, H.34, H.41
- PCB:
 design issues, 7.25-50
 dielectric absorption, 7.45
 dynamic effects, 7.44-45
 effects, 7.25
 grounding, 7.25
 guarding, 7.41
 using SOIC surface mount "R" package,
 7.44
 microstrip transmission line, 7.36
 MINIDIP op amp guard layout, 7.43-44
 resistance, calculation, 7.26
 see also Printed circuit board
 signal transmission, optimization
 techniques, 7.39-40
 skin effect, 7.35
 ground plane, 7.35
 SOIC op amp guard layout, 7.43-44
 static effects, 7.40-42
 stray capacitance, 7.44
 surface coating, 7.41
 surface leakage, 7.41
 trace resistance, 7.27
- Peak spectral spur, 3.19
- Pearlman, Alan, H.31, H.33
- Pease, Bob, H.26, H.34, H.41, H.43, H.72,
 7.99
- Pease, Robert A., H.41, 7.22, 7.164
- Pederson, D.O., 7.163
- Pentode, H.10
- Pfister, C., H.25
- PGA, 2.31-42
 alternate configuration, 2.33
 applications, 2.31, 2.34-41
 DAC programmed, 2.36-37
 in data acquisition systems, 2.32
 design issues, 2.32-33
 differential input, 2.38-40
 location in circuit, 2.32
 low noise, 2.35-36
 poor design, circuit, 2.33
 single supply instrumentation, circuit,
 2.39
- pH monitor, 4.39
- pH probe buffer amplifier, 4.66
- Phase characteristic, composite amplifier,
 6.202
- "Phase funnies," 6.203
- Phase response:
 change with frequency, 5.16
 filter, 5.14-16
 notch filter, 5.15
 versus frequency, 5.15
- Phase specifications, 6.96
- Philbrick Solid-State Operational
 Amplifiers, H.41
- Philbrick, George, H.31, H.33-34, H.43
- Philbrick, George A., H.13, H.16, H.20-21,
 H.24, H.41
- Phonograph, audio preamplifier, 6.11-27
- Photoconductive photodiode, 4.40
- Photocurrent, 4.39
- Photodiode 1991 Catalog, 4.67
- Photodiode:
 circuit noise performance, summary, 4.55
 circuit tradeoffs, 4.56
 current, in picoamperes, 4.43
 current generation, 4.39
 current noise density, 4.52
 current-to-voltage converter, 4.41
 dark current, 4.59
 equivalent circuit, 4.40
 equivalent noise bandwidth, 4.61
 high speed
 I/V converter, compensation, 4.57-58
 preamp design, 4.59-60
 preamp noise analysis, 4.61-62
 high speed preamp, FET input op amp,
 selection, 4.59
 with JFET op amp, 4.42
 operating modes, 4.40
 parasitic currents, 4.43
 photoconductive, 4.40, 4.59
 photosensitivity, 4.41
 photovoltaic, 4.40
 preamplifier, 4.39
 critical leakage paths, 4.44
 design, 4.39-48
 noise, 4.51-53
 sensitivity, 4.39
 sensor, 4.3
 SNR, 4.42
 voltage noise density, 4.52
 wideband, I/V converter, op amp

■ OP AMP APPLICATIONS

- selection, 4.58-59
- Photovoltaic photodiode, 4.40
- Pi-network, 7.114
- Piecewise linear amplifier:
 - with AD8037 clamped amplifier, 6.177-178
 - circuit, 6.177
- Piezoelectric sensor, 4.3, 4.39, 4.62
 - output conditioning, 4.30
- Piezoelectric transducer, 4.27, 4.30
 - circuit, 4.64
 - pressure, use, 4.32
 - reduced supply voltage, lower bias current, 4.64
- Piezoresistive effect, in semiconductor strain gage, 4.29
- Pin-programmable-gain in-amp, 2.17
- Pinchoff voltage, H.65
- Pippenger, Dale, H.69
- Pitot tube, 4.32
- Pixel, definition, 6.97
- Planar IC process, invention, H.29-30
- Plastic film capacitor, 5.103
- Plate electrode, H.1
- Plug-in breadboard system, 7.153
- PM1008, super-beta op amp, H.53
- PM1012, super-beta op amp, H.53
- Polycarbonate capacitor, 5.102, 5.104
- Polyester capacitor, 5.102, 5.104
- Polypropylene dielectric, 5.102, 5.104
- Polystyrene dielectric, 5.102, 5.104
- Pontis, George, 6.77
- Popcorn noise, 1.80
- Posthumus, K., H.3
- Potentiometer, 7.8-10
 - digitally addressable (RDAC), 7.14
- Power Consideration Discussions, 7.108
- Power dissipation, power supplies, 1.92
- Power line decoupling, resonant circuit, 7.19
- Power supply:
 - conditioning techniques, summary, 7.72
 - and decoupling, 1.92
 - noise reduction and filtering, 7.64
 - tools, 7.64
 - op amp, 7.51-74
 - power dissipation, 1.92
 - regulation, 7.51
- Power supply rejection, see PSR
- Power-down sequencing circuit, multiple supply applications, 6.170-171
- Practical Analog Design Techniques, Chapters 1, 2, and 4, 6.137
- Practical Design Techniques for Sensor Signal Conditioning, 2.29, 2.41, 2.51
- Preamplifier:
 - AC design, bandwidth, and stability, 4.50-51
 - audio, 6.1-27
 - microphone, 6.1-10
 - electret interface, 6.4
 - single-ended, single-supply high-impedance, 6.2-3
 - circuit, 6.2
 - noise model, 4.53
 - offset voltage, drift analysis, 4.48-49
 - RIAA phone, 6.11-26
 - signal frequency response, 6.1
- Precision bipolar IC op amps, H.55-59
- Precision bipolar op amp, noise, 1.101
- Precision Bipolar Op Amp Has Lowest Offset, Drift, H.68
- Precision bridge amplifier, using in-amp, circuit, 2.25
- Precision in-amp:
 - data, 2.23
 - remote load driver, circuit, 2.28
- Precision JFET IC op amp, H.60-66
- Precision Low Noise Low Input Bias Current Operational Amplifiers OP1177/OP2177 Data Sheet, H.69
- Precision Micropower Single-Supply Op Amps Have 100- μ V max Offset, H.69
- Precision Monolithics Incorporated, H.53-54, H.55-56, H.61
- Precision Op Amp, H.68
- Precision Resistor Co., Inc., 4.67, 7.22
- Precision single-supply composite in-amp, 2.13-15
 - gain expression, calculation, 2.14
 - rail-to-rail output, circuit, 2.14
- Precision voltage controlled current source, in-amp, 2.26-27
- Pressure:
 - measurement, 4.27-37
 - differential, 4.32
- Pressure transducer:
 - liquid and gas pressure measurement, 4.32
 - piezoelectric, use, 4.32
- The Pressure, Strain, and Force Handbook, 4.37
- Printed circuit board:
 - controlled impedance traces, 7.131-132
 - design, and EMI/RFI, 7.130-136
 - embedding traces, 7.135-136
 - microstrip transmission lines, 7.131-132
 - parasitics, 7.150
 - see also PCB
 - symmetric stripline transmission lines, 7.134-135
 - transmission line termination, 7.136
- Programmable gain amplifier, 2.31-42
 - with arbitrary attenuation step size, 6.182-183
 - circuit, 6.182
 - see also PGA
 - using AD813 current feedback video op

- amp, 6.126
 - Programmable pulse generator:
 - using clamping amplifier, 6.171-172
 - circuit, 6.171
 - Prototyping:
 - analog, key points, 7.153
 - debug, 7.153-155
 - digital systems, 7.153
 - DIP packages, 7.159
 - milled PCB, 7.157-158
 - and multilayer PCBs, 7.159
 - op amp functions, 7.139-164
 - solder-mount, 7.155-156
 - techniques, 7.153-162
 - Pseudo differential circuit, 6.66
 - Pseudorandom chopping frequency, 1.99
 - PSpice diode, 7.77
 - PSpice Simulation software, 7.164
 - PSRR:
 - op amp, 1.89-92
 - specification, 1.91
 - test setup, 1.91
- Q**
- Quad JFET, Single-Supply Op Amp, H.70
 - Quad Op Amp, H.68
 - Quad-core op amp stage, 1.111-112
 - Quality factor:
 - definition, 7.20
 - inductors, 7.20
 - Quantization:
 - error signal, 3.10
 - noise, in data converters, 3.10-11
 - size of LSB, table, 3.7
- R**
- Radio receiver, automatic gain control, 6.153
 - Ragazzini, John, H.16, H.26, 1.20
 - Rail bypass/distribution filter, 7.70
 - Rail-rail input op amp, 1.40-43
 - bipolar transistor
 - diagram, 1.41
 - offsets, 1.41-42
 - RAMDACs, 6.97
 - Randall, Robert H., H.26, 1.20
 - Rappaport, Andy, 7.22
 - Raster scan, definition, 6.97
 - Ratiometric drive, bridge, 4.12
 - Ratiometric reference, 4.23
 - Kelvin sensing, diagram, 4.24
 - Ratiometric voltage output temperature sensor, 4.89-90
 - RCA, H.61
 - RCD Components, Inc., 7.22
 - RDAC, digitally addressable potentiometer, 7.14
 - REAC, H.17
 - Received signal strength indicator, 6.153
 - Receiver, audio line stage, 6.28
 - Recognition of Harold Black, H.25
 - Recognition of M9 Designers C.A. Lovell, D.B. Parkinson, and J.J. Kuhn, H.25
 - Rectification, calculations, 7.123-125
 - Rectifier:
 - full-wave, using clamping amplifier, 6.172-173
 - single-supply half and full-wave, 6.167
 - two-element vacuum tube-based, H.1
 - Reeves Instrument Corporation, H.17-18
 - Reference terminal, non-inverting input, 1.7
 - Referred-to-input, see RTI
 - Referred-to-output, see RTO
 - Reflectance, shielding, 7.116-117
 - Regulated output charge-pump voltage converter, 7.62
 - Regulated voltage, calculation, 7.54
 - Regulation, linear IC, 7.52
 - Regulator:
 - linear, op amp power supply, 7.51
 - switching, op amp power supply, 7.51
 - Reichenbacher, P., 7.22, 7.50
 - Reine, Steve, 7.163
 - Resistance:
 - conductor, 7.26-27
 - measurement, 4.8
 - Resistance bridge, 4.8
 - Resistance temperature detector, 4.70, 4.78-81
 - configuration, 4.80
 - as passive sensor, 4.78
 - temperature and Seebeck coefficients, plot, 4.78
 - voltage drop in lead wires, 4.79
 - Resistor, 7.8-10
 - absolute temperature characteristic, 7.9
 - aging, 7.13
 - carbon composition, 7.9
 - comparison chart, 5.105
 - in difference amplifier, 2.3
 - excess noise, 7.13-14
 - failure mechanisms, 7.13
 - filter problem, 5.101-105
 - high input/output ratio, and CMR, 6.32
 - interconnection stability, 7.10
 - Johnson noise, 1.76
 - mismatching, 7.8
 - noise index, 7.14
 - nonlinearity errors, 7.9
 - parasitics, 7.10-11
 - selection criteria, 7.15
 - in subtractor amplifier, 2.3
 - temperature retrace, 7.10
 - thermal EMF, 7.11
 - thermal turbulence, 7.13
 - thermocouples, in construction, 7.12

■ OP AMP APPLICATIONS

- thermoelectric effect, 7.11-13
 - types, noise minimization, 7.14
 - voltage sensitivity, 7.13
 - wirewound, parasitics, 7.10-11
 - Resistor Johnson noise, 4.52-53
 - Response curves, filters, 5.26-49
 - RFI rectification:
 - input devices, sensitivity, 7.123
 - input-stage sensitivity, 7.122
 - reduction, in op amp and in-amp circuits, 7.126
 - relation to interfering signal, 7.125
 - RFI Rectification Test Configuration, 7.122
 - RFI/EMI, see EMI/RFI
 - RGB, color signals, control system, diagram, 6.96
 - RIAA:
 - basics, 6.11-13
 - idealized frequency response, table, 6.13
 - preamp, ideal, 6.12
 - time constants, ascending frequency, 6.12
 - RIAA equalizer:
 - active feedback, circuit, 6.17
 - capacitors, tolerances, 6.15
 - equalization curve, 6.11
 - equalization networks, 6.14-16
 - manufacturing tolerance, 6.14-15
 - network comparison, 6.14
 - resistors, 6.15-16
 - selection tolerance, 6.14
 - topologies, 6.16-26
 - topology-related parasitics, 6.15
 - RIAA preamp:
 - moving coil, DC-coupled active feedback, error versus frequency, 6.23
 - moving magnet
 - AC-coupled active feedback, circuit, 6.21
 - DC-coupled active feedback circuit, 6.18
 - error versus frequency, 6.19
 - passively equalized, error versus frequency, 6.26
 - phono, 6.11-26
 - topology
 - actively equalized, 17-23
 - passively equalized, 6.24-26
 - RIAA, Standard Recording and Reproducing Characteristic, Bulletin E1, 6.27
 - Rich, Alan, 6.77, 7.50, 7.137
 - Richter, Walther, H.11, H.23
 - Ringing, 6.89, 7.19, 7.150
 - macromodel, 7.145
 - Riskin, Jeff, 2.29, 6.47
 - RMS noise, 1.80-83
 - calculation, 1.81
 - Robege, J.K., 1.93
 - Roedel, Jerry, H.27
 - Ross, Ian M., H.41
 - Rostky, George, H.26
 - RS-232 device, ESD testing, 7.97
 - RS-485 device, ESD testing, 7.97
 - RTD, see also Resistance temperature detector
 - RTI noise, op amp, 3.12
 - RTO noise, op amp, 3.12
 - Rudin, Marv, H.53
 - Russell, Frederick A., H.26, 1.20
 - Russell, Rod, H.61
 - Russell, Ronald, H.49, H.67
 - Russell, Ronald W., H.69
- ## S
- S-plane, filter, 5.5-6
 - S/N+D, see SINAD
 - Sallen-Key bandpass filter, design equations, 5.84
 - Sallen-Key filter:
 - configuration, 1.119
 - design, 5.67-69, 5.115-117
 - distortion, 5.107-109
 - op amp limitations, 5.106
 - to lowpass, 5.119
 - transformation, 5.119-120
 - Sallen-Key highpass filter, design equations, 5.83
 - Sallen-Key lowpass filter, design equations, 5.82
 - Sallen, R.P., 5.133
 - Sample-and-hold, see SHA
 - Sample-to-hold mode transition, 3.31
 - Saturation, color, 6.96
 - Sawtooth waveform, 3.10
 - Schade, Otto Jr., H.69
 - Scharf, Brad, H.65
 - Scharf, Brad W., H.70
 - Schmitt, O.H., H.23
 - Schmitt, Otto, H.10-11
 - Schottky diode, 1.70-71, 2.24, 3.40, 6.122, 7.76-77, 7.85
 - Schottky noise, 1.77
 - Schultz, Donald G., 1.93, 1.127, 4.67
 - Schwartz, Tom, H.68
 - Schweber, Bill, H.68
 - Scouten, Charlie, H.43
 - SD-020-12-001, photodiode, 4.41
 - SECAM, color subcarrier frequency, 6.95
 - Second order allpass filter:
 - design, 5.80
 - design equations, 5.100
 - Second-order filter, responses, 5.13
 - Second-order system, 4.57-58
 - Seebeck coefficient:
 - of RTD, plot, 4.78
 - thermocouple, versus temperature, 4.72
 - Type S thermocouple, 4.78

- SEL resistors, H.31
- Selection guide for digital potentiometers, 7.22
- Selection Handbook and Catalog Guide to Operational Amplifiers, H.42
- Semiconductor strain gage, 4.29-32
 - piezoresistive effect, 4.29
- Semiconductor temperature sensor, 4.70, 4.84-90
 - BJT-based, relationships, 4.84
 - cold junction compensation, 4.75
- Sensor:
 - active, 4.1-2
 - applications, 4.4
 - characteristics, 4.2
 - classification, 4.1-2
 - high impedance, 4.39-67
 - output, 4.2-3
 - passive, 4.1
 - resistive elements, 4.7
 - self-generating, 4.1
 - signal conditioning, 4.1-91
 - temperature, 4.69-92
 - Brokaw cell, 4.85
 - current output, 4.86-88
 - characteristics, 4.87
 - driving resistive load, 4.87
 - Kelvin-scaled, 4.87
 - ratiometric voltage output, 4.89-90
 - semiconductor, 4.84-90
 - voltage output, 4.86-88
 - uses, 4.1
- Settling time:
 - definition, 1.69
 - diagram, 1.69
 - measurement, using "false summing mode," 1.70
 - thermal effects, 1.70
- 702, first monolithic IC op amp, H.45
- 709, monolithic IC op amp, H.45-46
- 741, monolithic IC op amp, H.48-49
- SFDR, 3.14, 3.19
 - definition and plot, 3.19
 - multi-tone, 3.19
 - out-of-band, versus upstream line power, plots, 6.160
 - plots, 6.143
- SHA:
 - CMOS, switched capacitor input, circuit, 3.30
 - hold mode, 3.30
 - track mode, 3.30
- Shannon, Claude, H.15
- Sheingold, Dan, H.7, H.21, H.27, H.35, H.37, H.42, H.43, H.71, 1.20, 1.93, 4.25, 4.37, 4.67, 4.91
- Shielding:
 - and cables, 7.118-121
 - effectiveness, calculation, 7.117
 - EMI/RFI, reduction, 7.115-121
 - impedance mismatch, 7.116
 - principles, 7.116-118
 - review, 7.115-121
- Shockley, W., H.29, H.41
- Shot noise, 1.77
 - spectral density, 1.77
 - voltage, 6.149
- Sigma-delta ADC, high resolution, driving, 3.24-25
- Signal amplifier, applications, 6.1-207
- Signal bandwidth, 4.51
- Signal cabling, mutual inductance and coupling, 7.18
- Signal conditioning, sensors, 4.1-91
- Signal gain, 6.84
- Signal leads, voltage drop, 7.27-28
- Signal return currents, 7.27-45
- Signal-to-noise ratio, see SNR
- Signal-to-noise-and-distortion ratio, see SINAD
- Silicon bandgap voltage reference, Brokaw cell, 4.85
- Silicon Detector Corporation, 4.67
- Silicon Detector photodiode, 4.41
- Silicon transistor, invention, H.29
- Siliconix PAD/JPAD/SSTPAD series Low Leakage Pico-Amp Diodes, 7.99
- Simons, Elliott, 6.187
- Simple line receiver:
 - audio, 6.33-34
 - diagram, 6.33
 - function implementation, 6.35
 - load balance, 6.35
 - topology, diagram, 6.36
- Simulation:
 - analog circuit, 7.139-140
 - caveats, 7.149
 - and CMRR, 7.149
 - effectiveness, 7.151-152
 - op amp functions, 7.139-164
 - versus breadboarding, 7.148-149
- SINAD, 3.14, 3.15-16
 - definition, 3.15
 - and ENOB, 3.15
 - and THD+N, 3.15
- Single pole filter, design equations, 5.81
- Single pole RC, design, 5.60
- Single-chip thermocouple signal conditioner, 4.77-78
- Single-ended current-to-voltage conversion, 3.50-51
- Single-ended line driver, 6.55-64
 - consumer equipment, 6.55-56
- Single-ended, single-supply high-impedance microphone preamp, 6.2-3
- Single-supply AC-coupled composite video

■ OP AMP APPLICATIONS

- line driver, 6.134-135
- circuit, 6.134
- Single-supply AC-coupled differential driver, circuit, 6.136
- Single-supply AC-coupled single-ended-to-differential driver, 6.136
- Single-supply data acquisition system, circuit, 2.26
- Single-Supply FET, H.70
- Single-supply in-amp, data, 2.23
- Single-supply instrumentation PGA, circuit, 2.39
- Single-supply RGB buffer, circuit, 6.130
- Single-supply video:
 - AC-coupled, headroom considerations, 6.133
 - applications, 6.130-136
 - line driver, low distortion, zero-volt output, 6.132
 - sync stripper, circuit, 6.131
- Skin effect, 7.34-35
- Slattery, W., 5.134
- Slew limiting, 1.68
- Slew rate, 1.68-69
 - summary, 1.69
- SM3087, H.31
- Small, James S., H.13, H.24
- Smart sensor, 4.4
- Smith, Lewis, 1.93, 4.67
- Smith, Lewis R., H.35, H.42
- Smoke detector, 4.39
- SNR, 3.14, 3.15-16
 - calculation, 3.10
 - definition, 3.15
- Soakage, 7.2-3
- Socket, disadvantages, 7.158
- Socketlov, Steve, 7.22
- Soderquist, Donn, H.68, 1.51
- SOIC, surface mount package, 4.45-46
- Solder, low thermal EMF, 4.49
- Solder-Mount, prototyping system, 7.155-156
- Solid state current feedback op amp, Bell Labs, diagram, 1.28
- Solomon, James, H.49, H.67
- Solomon, James E., H.72
- Solomon, Jim, H.51
- Southern and F-Dyne film capacitors, 7.22
- Specialty amplifier, 2.1-51
- Specification MIL-PRF-123B, Capacitors, Fixed, Ceramic Dielectric..., 7.22
- Specification MIL-PRF-19978G, Capacitors, Fixed, Plastic..., 7.22
- SPICE:
 - analog circuit simulation program, 7.139-140
 - and breadboarding, 7.148-149
 - model authors, 7.152
 - noise generator, diagram, 7.146
 - simulation, useful points, 7.152
 - support, 7.152
- SPICE evaluation, in-amp with 290MHz gain-bandwidth, 6.181
- Spurious free dynamic range, 6.143
 - see also SFDR
- SS bipolar op amp, output phase-reversal, 7.90
- SSM2141:
 - active line receiver circuit, 6.42
 - audio line receiver, 2.5-6
 - difference amplifier, 2.4-5
 - line receiver, 6.108
 - low distortion, high CMR audio line receiver, 6.35
- SSM2142:
 - balanced line driver, 6.108
 - cross-coupled differential line driver, 6.67-68
 - THD+N versus frequency, plots, 6.68
- SSM2143:
 - active line receiver circuit, 6.42
 - audio line receiver, 2.5
 - difference amplifier, 2.4-5
 - line receiver, 6.108
 - low distortion, high CMR audio line receiver, 6.35
- SSS725, precision bipolar op amp, H.53, H.55-56
- Standard IPC-2141, "Controlled Impedance Circuit Boards and High Speed Logic Design," 7.137
- Staniforth, Alan, 7.137
- Star ground, 7.31
- Stata, Ray, H.35, H.37, H.42, 1.20-21
- State variable filter:
 - design, 5.72-73, 5.116
 - equations, 5.88-90
 - op amp limitations, 5.106
- Step response:
 - filter, 5.18
 - curves, 5.28-38
- Stephens, M., 6.10
- Stopband filter, 5.2-3
- Storch, L., 5.133
- Stout, D., 1.93, 6.27
- Strain, measurement, 4.27-37
- Strain gage, 4.8, 4.27
 - bonded, 4.28
 - advantages, 4.28
 - bridge, in beam force sensor, diagram, 4.30
 - comparison of metal and semiconductor, 4.30
 - foil-type, 4.29
 - low-impedance device, 4.31
 - semiconductor, 4.29-32
 - sensor, 4.3

- sensor amplifier, circuit, 4.33
 - unbonded, 4.27
 - operating principles, 4.28
 - uses, 4.30
 - wire sensing elements, 4.29
 - Stray capacitance, 7.46-49
 - PCB, 7.45
 - Strip inductance, 7.16
 - Stripline:
 - symmetric
 - for PCB transmission, 7.134-135
 - propagation delay, 7.135
 - Subtractor amplifier, 2.3-6
 - Sullivan, Doug, H.69
 - Sullivan, Douglas, H.60
 - Summing Amplifier, H.14
 - Summing point, 1.8
 - Super-beta bipolar input bias current
 - compensated op amp, circuit, 1.38
 - Super-beta bipolar transistor technique, H.51
 - Surface microstrip, 7.131-132
 - Suttler, Goodloe, 4.92
 - Swartzel M9 design, H.17
 - Swartzel op amp, diagram, H.14
 - Swartzel, Karl, op amp, H.14-15
 - Swartzel, Karl D. Jr., 1.20
 - Swartzel, K.D. Jr., H.25
 - Switch, buffered video crosspoint, 6.129
 - Switching regulator, 7.64
 - op amp power supply, 7.51
 - Switching time, multiplexer, 3.26
 - Sync inserter, with AD8037 clamping amplifier, 6.176-177
 - System offset minimization, 4.22-24
- T**
- T-Tech, Inc., 7.164
 - T10 prototype gun director, H.13
 - Tadewald, T., 7.22, 7.50
 - Tantalum and Ceramic Surface Mount Capacitor Catalog, 7.22
 - Tantalum electrolytic capacitor, 7.7-8, 7.65
 - for EMI/RFI protection, 4.88
 - Tantalum Electrolytic and Ceramic Capacitor Families, 7.73
 - TDN: Temperature Drift Nonlinearity--A New Dual-FET Specification, 6.207
 - Teal, Gordon, H.29
 - Teflon dielectric, 5.102, 5.104
 - Teflon standoff, 4.47-48
 - Teledyne Corporation, H.34
 - Television:
 - monochrome, standard, 6.94
 - picture frame, fields, 6.93
 - standard broadcast interface format, 6.93
 - Tellegen, B.D.H., H.3, H.6
 - Temperature coefficient, capacitor, 7.6
 - Temperature control loop, diagram, 4.4
 - Temperature differential, calculation, 7.102
 - Temperature retrace, resistors, 7.10
 - Temperature sensor, 4.69-92
 - current output, 4.86-88
 - ratiometric voltage output, 4.89-90
 - semiconductor, cold junction
 - compensation, 4.75
 - voltage output, 4.86-88
 - Temperature transducer, types, 4.69
 - Terman, F.E., H.7
 - Terman, Frederick, H.5
 - Terman, Frederick E., 1.20, 1.29
 - Texas Instruments, H.29, H.31, H.61-62
 - Thandi, Gurgit, 7.73
 - THD+N, 3.14, 3.17-18
 - definition, 1.88, 3.17-18
 - and SINAD, 3.15
 - THD, 3.14, 3.17-18
 - definition, 1.88, 3.17
 - Thenevin equivalent, 4.89
 - Thermal EMF, resistors, 7.11
 - Thermal management, op amps, 7.101-108
 - Thermal noise, resistors, 7.13
 - Thermal relationships, chart, 7.102
 - Thermal resistance, 7.101
 - junction to ambient air, measurement, 7.102
 - Thermal voltage, 1.105
 - Thermalloy 2227, 6.49
 - Thermistor, 4.81-83
 - definition, 4.81
 - fixed shunt resistors, 4.82-83
 - high sensitivity, 4.82
 - linearization, 4.82-83
 - resistance characteristics, plot, 4.81
 - sensor, 4.3
 - Thermocouple:
 - basic operating principles, 4.73
 - characteristics, 4.70
 - cold junction reference system, 4.74
 - EMF, effects, 7.12
 - metals, 4.71
 - output voltage definition, 4.74-75
 - output voltage versus temperature, 4.71
 - parasitic, 4.22, 7.11
 - principles, cold-junction compensation, 4.70-76
 - Seebeck coefficient, 4.72
 - sensor, 4.2, 4.3
 - single-chip, signal conditioner, 4.77-78
 - termination, circuit, 4.75
 - thermoelectric EMF, 4.73
 - Type J, 4.71-72
 - Type K, 4.71-72, 4.76
 - amplifier and cold junction compensator, 4.76
 - Type S, 4.71-72

■ OP AMP APPLICATIONS

- voltage generation, 4.74
- Thermoelectric effect, resistors, 7.11-13
- Thermoelectric EMF:
 - and dissimilar metals, 4.74
 - thermocouple, 4.73
- Thermoelectric voltage:
 - generation, 4.49
 - as input offset voltage source, 4.49
- Thin film resistor, for precision amplifiers, 1.48
- Thomas, L.C., 5.133
- Three op amp in-amp:
 - circuit, 2.11-12
 - single supply, restrictions, 2.13
- Tim Williams Website, 7.138
- Time domain response:
 - filter, 5.17-18
 - impulse response, 5.17-18
- Timko, Mike, 4.91-92
- TL06x, H.62
- TL07x, H.62
- TL08x, H.62
- TMP35:
 - SO-8 packaged voltage output temperature sensor, 4.88
 - voltage output sensor, 4.76
- TMP36, TO-92 packaged voltage output temperature sensor, 4.88
- TN56, H.36
- TO-99, for ICs, 6.49
- TO-99 package, diagram, 4.47
- Todd, C., 6.10
- Toennies, J.F., H.10, H.23
- Toomey, P., 5.134
- Total harmonic distortion, 1.88
 - see also THD
- Total harmonic distortion plus noise, see THD+N
- Total noise, in-amp, calculation, 2.21
- Total output error, calculation, 1.61
- Total output noise:
 - calculations, 1.83-87
 - in-amp, calculation, 2.21
- Tow, J., 5.133
- Townsend, Jeff, H.65
- TQ56, H.36
- Tran, Chau, 6.187
- Transconductance, 1.104
- Transducer, 4.2
 - output voltage range, 2.31
 - temperature, types, 4.69
- Transformer:
 - analog accuracy, 2.44
 - in audio line coupling, 6.28-29
 - coupling, 3.36
 - driver, galvanic isolation, 6.29
 - effective voltage gain, 6.6
 - impedance ranges, 6.6
 - as isolation amplifier, 2.43
 - non-premium core, higher distortion, 6.71
 - optimum turns ratio, calculation, 6.6
- Transformer Application Notes (various), Jensen Transformers, 6.77
- Transformer-coupled line driver, 6.69-76
 - basic, 6.69-70
 - feedback, 6.71-76
- Transformer-coupled microphone preamp, 6.5-7
 - THD+N, 6.7
- Transformer-input line receiver, 6.44-46
 - circuit, 6.44
 - CMR errors, plot, 6.45
- Transient voltage suppressor, 2.24, 7.98
- Transimpedance, 5.109
- Transimpedance op amp, 1.24, 1.114
- Transistor:
 - germanium, limitations, H.29
 - invention, H.29
 - packaged dual types, 6.194
- Transitional filter, 5.22
- Transmission line, 7.36
 - behavior, summary, 6.101
 - driver, experiments, 6.102-105
 - microstrip, 7.36
 - termination, rule, 7.136
- TransZorb, 7.98
 - availability, 7.100
 - clamp, 7.88
- Trefleaven, D., 5.134
- Triboelectric effect, 7.91
- Trietley, Harry L., 4.37
- Tucker, D.G., H.6
- Twin T notch filter:
 - design, 5.75
 - design equations, 5.94
 - schematic, 5.132
- Two op amp in-amp:
 - circuit, 2.7
 - CMR, 2.7, 2.8
 - disadvantages, 2.8-9
 - single-supply, restrictions, 2.8-9
- Two Precision Dual Op Amp Families, H.68
- Two-tone IMD, see also Two-tone intermodulation distortion
- Two-tone intermodulation distortion, 3.14, 3.19
- 210, chopper op amp, H.36
- 211, chopper op amp, H.36
- 220, chopper op amp, H.36
- 232, chopper op amp, H.36
- 233, chopper op amp, H.36
- 260, chopper op amp, H.36
- Type 5MC Metallized Polycarbonate Capacitor, 7.73
- Type EXCEL leaded ferrite bead EMI filter, and Type EXC L leadless ferrite bead, 7.73

Type HFQ Aluminum Electrolytic Capacitor
and Type V Stacked Polyester Film
Capacitor, 7.73

U

Understanding Common Mode Noise, 7.137

Unregulated inverter charge-pump voltage
converter, 7.61

V

Vacuum tube:

current feedback, 1.26-28

feedback circuit

CFB gain-bandwidth relationship,
plots, 1.27

current feedback, 1.27

Terman designed, 1.26

Valley-Wallman MIT Radiation Laboratory
textbook, H.5

Valley, George E. Jr., H.7, H.26

Van Valkenberg, M.E., 5.133

Varactor bridge solid state op amp, H.33-35
block diagram, H.34

Variable gain amplifier:

in automatic gain control, 6.153

digitally controlled, for CATV upstream
data line drivers, 6.157-158

Vector Electronic Company, 7.164

Vectorboard, prototyping system, 7.153

Venturi effect, 4.32

Verhagen, C.M., H.12, H.24

Vertical sync, 6.94

Very low noise transformer-coupled

microphone preamp, 6.8-9

circuit, 6.8

THD+N, 6.9

Video:

amplifier, 6.93-138

bandwidth, 6.98-100

color signal, matrix unit, 6.95

composite color signal, 6.95

differential driving/receiving,
approaches, 6.109

distribution amplifier, 6.107

formats, 6.96-97

high-speed multiplexing, 6.124-126

line driver, 6.106-107

NTSC composite color line, diagram, 6.94
signal

analog television lines, 6.94

processing method, 6.108

and specifications, 6.93-95

transmission, 6.101

single-supply

applications, 6.130-136

RGB buffer, 6.130-131

standard broadcast format, 6.93

Video amplifier, 6.93-138

Video line driver, single-supply AC-coupled

composite, 6.134-135

Video multiplexer:

dual RGB source, 6.128

with three 2:1 multiplexers, diagram,
6.128

Video Op Amp, 1.51

Virtual ground, 1.8

Vishay chip resistors and type VTF networks,
6.137

Vishay VTF series part 1005, 6.115

Vishay-Ohmtek firm, resistors, 6.34

Vishay/Dale Resistors, 7.23

Vishay/Dale RNX Resistors, 4.67

Vladimirescu, A., 7.163

Vladimirescu, Andrei, 7.163

Voigt, Paul, H.3

Voigt, Paul G.A.H., H.6

Voltage, regulated, calculation, 7.54

Voltage controlled amplifier, 6.154-156
circuit, 6.154

Voltage converter:

charge-pump, 7.59-60

regulated output charge-pump, 7.62

Voltage doubler, 7.59-60

Voltage drop, signal leads, 7.27-28

Voltage feedback, in macromodel, 7.141

Voltage feedback op amp, 1.104-112

comparison with current feedback op amp,
1.124-125

frequency response, 1.72-74

gain-bandwidth product, 1.72-74

plots, 1.72

gain-bandwidth product, 1.72-74

input impedance, diagram, 1.62

Voltage inverter, 7.59-60

Voltage noise, 6.149

Voltage output temperature sensor, 4.86-88

Voltage regulator:

adjustable, 7.54

adjustable voltage LDO, 7.58-59

fixed voltage LDO, 7.57-58

functional diagram, 7.53

LDO regulator controller, 7.59

linear

adjustable regulator ICs, 7.55

basics, 7.52-54

negative leg series style, 7.52-53

positive leg series style, 7.52-53

three terminal, diagram, 7.53

noise reduction, 7.58

pass device, 7.54

Voltage sensing, feedback, 7.27

Voltage standing wave ratio, filter, 5.24

Voltage-boosted rail-rail output driver,
6.193-195

circuit, 6.193

■ OP AMP APPLICATIONS

W

Wadell, Brian C., 7.138
Wagner, Richard, H.68, 1.51
Wainwright Instruments, 7.155
Wainwright Instruments GmbH, 7.164
Wainwright Instruments Inc., 7.164
Wallman, Henry, H.7, H.26
Watkins, Tim, 7.163
Waveform:
 duty cycle, in AC-coupled single-supply
 op amp, 6.133
 positive swing portion, 7.84
Webster, John G., 4.25, 4.37, 4.67, 4.91
Weeks, J.R., H.25
Wesco film capacitors, 7.22
Western Electric Company, H.3-4
West, Julian M., 1.20
Wheatstone bridge, circuit, 4.8
Whitlock, B., 6.47
Whitney, Dave, H.66, H.70, 6.91, 6.137
Wide bandwidth noise generator, circuit,
 6.165
Wide dynamic range ultra low distortion
 driver, 6.58-59
Wideband in-amp, 6.184
Widlar, Bob, H.45-46, H.49, H.51-52, H.67,
 H.72
Widlar, R.J., H.67
Widlar, Robert J., H.67
Williams, A.B., 5.133
Williamsen, M., 5.134
Williams, Jim, H.67, 7.164
Williams, Tim, 7.137
Wilson, Garth, H.53
Wire inductance, 7.16

Wire sensing elements, in strain gage, 4.29
Wire-wrap, prototyping system, 7.153
Wong, James, 4.91, 7.22, 7.137
Worst harmonic, 3.14, 3.17-18
Wurcer, S., 2.29, 6.47, 6.77
Wurcer, Scott, H.62, H.65, H.66, H.70, H.71,
 4.1, 4.39, 6.77, 6.137, 6.207, 7.22,
 7.23, 7.50
Wynne, John, 6.187

X

X-AMP, 6.183
 continuous interpolation, current-
 controlled stages, circuit, 6.155
 exponential amplifier, 6.154
xDSL upstream data line driver, 6.158-160
XFCB 1.5, op amp fabrication process, 1.104
XFCB 2, op amp fabrication process, 1.104
XFET, 3.43

Z

ZDT651 SM-8 Dual NPN Medium Power
 Transistors Data Sheet, 6.207
ZDT751 SM-8 Dual PNP Medium Power
 Transistors Data Sheet, 6.207
Zener diode, H.56, 1.48, 7.79, 7.88, 7.98
 breakdown voltage, 7.79
Zener zap trimming, 1.36, 1.48
 advantages, 1.49
Zener zapping, H.56, H.61
Zhang, K., 7.163
Zicko, Peter, H.42
Zis, Jerry, H.54, H.71
Zumbahlen, H., 5.1, 5.134
Zverev, A.I., 5.133

ANALOG DEVICES' PARTS INDEX

- AD60X X-AMP series, 6.183
AD82X family, 6.3
AD108, H.52
AD108A, H.52
AD210, 2.44-46, 2.46
AD215, 2.47
AD260, 2.49-50
AD261, 2.49-50
AD301AL, H.50
AD503, H.60-66, H.63
AD504, H.54
AD506L, H.61
AD508, H.54
AD508K, H.54
AD509, H.66
AD513, H.61
AD515, H.63
AD515L, H.63
AD516, H.61
AD517, H.54
AD517L, H.54
AD518, H.66
AD524, 2.24
AD524C, 2.23
AD526, 2.34-35
AD542, H.62
AD542L, H.62
AD544, H.62
AD545, H.63
AD545L, H.63
AD546, H.64
AD547, H.62
AD547L, H.62
AD548, H.62
AD548k, H.62
AD549, H.64, 1.58, 1.78, 4.43, 4.47
AD549K, 4.42
AD549KH, 4.47
AD549KN, H.64
AD549L, H.64
AD588, 4.34-35
AD589, 4.33, 6.197, 6.200
AD590, 4.86, 4.92
AD592, 4.86-87
AD592CN, 4.87
AD594, 4.77-78
AD595, 4.77-78
AD600, 6.154-156
AD602, 6.154, 6.156
AD603, 6.154, 6.156
AD604, 6.154, 6.156
AD605, 6.154, 6.156
AD620, 2.12-15, 2.17, 2.19, 2.21-22,
2.24, 2.26-28, 2.30, 2.46, 4.14, 4.33,
7.87-89, 7.87-90, 7.128
AD620B, 4.34
AD621, 2.17, 2.22, 4.35, 7.128
AD621B, 2.23, 4.34
AD622, 2.23, 7.128
AD623, 2.16, 2.26, 2.39, 4.14, 6.186,
7.39, 7.90, 7.128
AD623B, 2.23
AD624C, 2.17, 2.23
AD625, 2.38-39
AD625C, 2.23
AD626, 2.23
AD626B, 2.23
AD627, 2.10-11, 2.39, 4.14, 7.90, 7.128
AD627B, 2.23
AD629, 7.39, 7.81-82
AD642, H.62
AD644, H.62
AD648, H.62
AD648KN, H.62
AD688, 1.66
AD704, H.54, 1.35
AD705, H.54, 1.35, 6.190
AD706, H.54, 1.35
AD707, H.57, 3.12, 3.25, 4.22
AD708, H.57, 4.16
AD711, H.62, 6.35, 6.191-192, 6.197,
6.199
AD711K, H.62
AD712, H.62, 1.103, 5.126, 6.35
AD712KN, H.62
AD713, H.62
AD741, H.50-51
AD741J, H.50
AD741L, H.50
AD743, H.65, 1.77, 1.79, 4.59, 4.64-66
AD743K, 1.54
AD744, H.66, 4.59, 6.35, 6.62-63
AD744JN, 6.62
AD745, H.65, 1.77, 1.79, 4.59, 4.63-66,
6.22, 6.24-25, 6.25
AD746, 6.35
AD768, 3.50
AD780, 3.34, 3.44, 6.122-123
AD795, H.64, 1.78-79, 4.43, 4.46, 4.51-
52, 4.56, 4.59, 7.82-83
AD795JR, 4.42-43, 4.48-49, 4.54, 4.56,
4.66
AD795K, 4.55
AD797, 2.35-36, 3.12, 3.25, 6.8-9, 6.23,
6.48, 6.58-59, 7.86, 7.122
AD797JN, 6.8
AD810, 6.48, 6.124
AD811, H.66, 1.103, 6.48-49, 6.50, 6.51,
6.60-64, 6.69, 6.82, 6.85, 6.106, 6.113,
6.171-172, 7.148

■ OP AMP APPLICATIONS

AD812, 6.48, 6.51, 6.60-61, 6.63-64, 6.106, 6.109-110, 6.113
AD813, 6.106, 6.110, 6.124, 6.126
AD815, 6.48, 6.63-64
AD817, 1.103, 6.48, 6.51, 6.54, 6.82, 6.88-89, 6.163, 6.166, 6.182, 6.184, 6.199-200, 6.204, 7.106, 7.144
AD818, 6.48, 6.54, 6.106, 6.115-116, 6.116
AD820, H.60-66, H.65, 1.41, 1.97, 4.45-46, 4.59, 6.3, 6.4, 6.24, 6.26, 6.167, 6.199, 7.78
AD820B, H.65, 4.42
AD820BN, 4.44, 4.45
AD822, H.60-66, H.65, 1.41, 1.97, 2.14, 6.2-4, 6.167
AD823, H.60-66, H.65, 1.40-41, 4.59, 4.60-61, 6.2-3, 6.42, 6.63-64
AD824, H.60-66, H.65, 1.41, 1.97
AD825, 5.128-129, 5.131, 6.41-43, 6.55, 6.63-64, 6.179, 6.199
AD826, 6.48, 6.51, 6.82, 6.89, 6.177-178
AD827, 6.89, 7.122
AD828, 6.106, 6.116, 6.181
AD829, H.66, 1.34-35, 6.48, 6.83, 6.165-166, 6.168-169
AD830, 6.117, 6.119, 6.179-181
AD840, H.66
AD843, 4.59, 6.190
AD844, 6.168
AD845, 4.59, 6.18, 6.19, 6.21, 6.25, 6.41-43, 6.48, 6.54, 6.60-61, 6.69, 6.72-73, 6.75-76, 6.87, 7.122
AD845, 1.111
AD846, H.66, 1.25, 1.28, 6.168
AD847, 1.110
AD847, H.66, 1.103, 5.110, 6.48, 6.89, 7.150
AD974, 3.27
AD976, 3.27
AD977, 3.27
AD8013, 6.110
AD76XX, 3.27
AD77XX, 2.32, 2.40, 3.24-25, 4.80-81
AD789X, 3.27
AD813X, 3.37, 3.51, 6.114
AD855X, 1.32
AD860X, 1.47
AD922X, 3.34, 3.36-37
AD976X, 3.48-49, 3.48-50
AD977X, 3.48-49, 3.48-50
AD1580, 6.197, 6.200
AD1853, 3.52
AD3554, H.40
AD7416, 4.87
AD7417, 4.87
AD7418, 4.87
AD7528, 5.128-129, 5.131
AD7730, 2.40, 4.23-24, 4.36
AD7776, 2.26
AD7816, 4.87
AD7817, 4.87
AD7818, 4.87
AD7846, 2.36-37
AD7890-10, 3.27
AD8001, H.66, 1.103, 1.117, 6.82, 6.86-87, 6.99-100, 6.102, 6.105, 6.106, 7.161-162
AD8002, 1.117, 6.106, 6.111-113
AD8004, 1.117, 6.100
AD8005, 1.117
AD8009, 1.103, 1.117
AD8010, 6.107
AD8011, 1.103, 1.115-117, 6.151
AD8012, 1.117, 6.106
AD8013, 1.117, 6.124
AD8014, 1.117
AD8015, 6.82
AD8016, 7.104-106
AD8016ARP, 7.104
AD8017, 7.106
AD8017AR, 7.101
AD8018, 6.159-160
AD8021, 6.83
AD8023, 1.117
AD8031, 1.112, 6.82, 6.132
AD8032, 1.112, 6.82
AD8036, 6.120-122, 6.171-172
AD8037, 6.120-123, 6.171-174, 6.176-178
AD8039, 1.71, 1.112
AD8041, 1.112, 3.34, 6.82, 6.130-131, 6.134-135
AD8042, 1.112, 6.82, 6.130, 6.136
AD8044, 1.112, 6.130-131
AD8047, 1.112, 6.106
AD8048, 1.112, 1.120, 6.106
AD8055, 3.49-50, 6.106, 6.116
AD8056, 6.106, 6.116
AD8057, 3.22-24, 3.34, 6.106, 7.106
AD8058, 3.22-24, 3.37, 6.106, 7.106
AD8061, 6.106
AD8062, 6.106
AD8063, 6.106
AD8065, 6.55, 6.61
AD8072, 1.117
AD8073, 1.117
AD8074, 1.112, 6.82, 6.98, 6.124
AD8075, 1.75, 1.112, 6.82, 6.98, 6.124
AD8079A/B, 6.82
AD8110, 6.129
AD8111, 6.129
AD8113, 6.129
AD8114, 6.129
AD8115, 6.129
AD8116, 6.129
AD8129, 6.117-118

- AD8130, 6.117-119
- AD8131, 6.114
- AD8138, 3.37-38, 6.114
- AD8170, 6.127-128
- AD8174, 6.127-129
- AD8180, 6.127
- AD8182, 6.127
- AD8183, 6.127
- AD8185, 6.127
- AD8323, 6.157-158
- AD8350, 6.152
- AD8351, 1.103, 1.104
- AD8367, 6.154, 6.156
- AD8531, 1.42, 1.46
- AD8532, 1.42, 1.46
- AD8534, 1.42, 1.46
- AD8541, 6.2, 6.192
- AD8551, 1.54, 1.99, 4.22, 4.76, 6.191-192, 7.38, 7.44
- AD8552, 1.99, 4.22
- AD8554, 4.22
- AD8571, 1.99-101
- AD8572, 1.99-101
- AD8574, 1.99-101
- AD8601, 1.47, 1.97
- AD8602, 1.47, 1.97
- AD8604, 1.47, 1.97
- AD8605, 1.54
- AD8610, 2.27, 6.55, 6.74-76, 6.195-196, 6.203
- AD8620, 6.76
- AD9002, 6.122
- AD9042, 3.28
- AD9203, 3.37-38
- AD9220, 3.16
- AD9225, 3.12-13, 3.31, 3.34-35
- AD9610, 1.28
- AD9611, 1.28
- AD9620, 6.81
- AD9630, 6.81
- AD9631, 1.112
- AD9632, 1.112, 3.12-13
- AD2210X, 4.89-90
- AD22100, 4.90
- AD22103, 4.89-90
- AD506J, H.60
- AD506k, H.60
- AD8554, 1.99
- ADG46X series, 7.81
- ADG408, 6.182
- ADG409, 2.38
- ADG412, 2.35-36
- ADG438, 7.81
- ADG439F, 7.81
- ADG465, 7.80
- ADG466, 7.80, 7.89
- ADG467, 7.80
- ADG508, 7.81
- ADG509F, 7.81
- ADG511, 2.39
- ADI Thermal Coastline, 7.55-56
- ADLH0032, H.40
- ADLH0033, 6.79
- ADM660, 7.61
- ADM8660, 7.61
- ADMXXX-E, 7.97-98
- ADP330X, 7.55-57
- ADP1148, 7.63
- ADP3300, 7.57
- ADP3300ART-5, 7.57
- ADP3300ART-YY, 7.57
- ADP3301, 7.57
- ADP3301AR-5, 7.57
- ADP3310-3.3, 7.63
- ADP3331, 7.58-59
- ADP3335, 7.58
- ADP3603, 7.60, 7.62
- ADP3604, 7.60, 7.62
- ADP3605, 7.60, 7.62
- ADP3607, 7.60
- ADR292E, 3.45
- ADV7120, 6.130-131
- ADV7121, 6.130
- ADV7122, 6.130
- AMP01, 2.28
- AMP02, 2.24
- AMP03, 2.28, 7.39, 7.82
- AMP04, 2.39
- AMP04E, 2.23
- anyCAP LDO regulators, 7.55, 7.57
- BUF03, 6.48-50, 6.80
- BUF04, 1.46, 6.9, 6.22, 6.35, 6.48-50, 6.59-61, 6.81-82
- HOS-100, 6.79
- MAT02, 6.197, 6.199-200
- OP05, H.55-56
- OP06, H.55-56
- OP07, H.53-54, H.55-59, 1.31, 1.36, 1.48, 1.78, 1.82, 4.42
- OP08, H.53
- OP12, H.53
- OP15, H.61
- OP16, H.61
- OP17, H.61
- OP27, H.58-59, H.65, 1.36-37, 1.78, 1.82, 4.65, 6.19, 6.166, 7.86, 7.143
- OP37, H.58, 6.22, 6.25
- OP42, 4.59, 6.19, 7.122
- OP77, H.57
- OP77A, H.57
- OP80, 7.122
- OP90, 5.110
- OP97, H.53-54, 1.35, 1.38, 2.27, 4.42, 6.26, 6.190, 6.193-195
- OP113, 1.32, 1.97, 2.36-37
- OP176, 5.108

■ OP AMP APPLICATIONS

OP177, H.57, 1.66-67, 1.81, 1.89, 1.91,
1.95, 1.101, 3.12, 3.25, 4.22, 4.33-35,
6.199, 7.12
OP177A, H.57
OP177F, 1.54, 1.58, 1.96-97
OP184, 1.42, 1.97
OP191, 1.42, 1.97
OP196, 1.97
OP200, 7.122
OP213, 1.32, 1.81, 1.97, 4.16, 4.35, 6.2-
3
OP249, H.62, 1.103, 6.35, 7.122, 7.145
OP270, 6.2, 6.19
OP275, 3.52, 6.2, 6.7, 6.21, 6.35, 6.38-
39, 6.48, 6.53-54, 6.56-57, 6.65, 6.72
OP279, 1.42
OP284, 1.42, 1.97
OP291, 1.42, 1.97
OP293, 1.97
OP296, 1.97
OP297, H.53-54, 1.35, 1.38, 7.122

OP413, 1.32, 1.97
OP470, 6.2
OP482, 1.103
OP484, 1.42, 1.97
OP491, 1.42, 1.97
OP496, 1.97
OP497, H.53-54, 1.35, 1.38
OP727, H.59, 1.95
OP747, H.59, 1.95
OP777, H.59, 1.95, 1.97, 4.76, 7.80
OP1177, H.59, 1.95, 4.22
OP2177, H.59, 1.95, 4.16
OP4177, H.59, 1.95
REF195, 4.35
SSM2135, 6.2-3, 6.4
SSM2141, 6.35-36, 6.38-39, 6.42, 6.108
SSM2142, 6.67-68, 6.108
SSM2143, 6.35-36, 6.41-42, 6.44-45, 6.108
TMP35, 4.76, 4.88
TMP36, 4.88
X-AMP, 6.154-156

STANDARD DEVICE PARTS LIST

- 6CS7 dual triode, H.11
 6J6 dual triode long-tailed pair, H.12
 6J7G pentode, H.11
 6L6, H.19
 6SJ7, H.19
 6SL7 dual triode, H.16-17, H.19
 12AU7, H.22
 12AX7 dual triode, H.20-21
 12AX7, 6.206
 12SH7 pentode, H.12
 1N748A, H.38
 1N914, glass diode, 7.77-78
 1N3600, H.39
 1N4148, H.36
 diode, 6.194
 glass diode, 7.78
 low capacitance diode, 7.87
 1N4448, diode, 6.69
 1N5235, 6.195
 1N5240B, zener diode, 7.78-79
 1N5711, Schottky type diode, 7.77
 1N5712, Schottky diode, 6.122
 2N760, H.31
 2N930, H.31
 2N1132, H.31
 2N2219A, 4.34
 2N2222, H.39
 2N2222A, H.38
 2N2907, H.31-32, H.39
 2N2975, H.36-37
 2N3250, H.38
 2N3904, H.39
 emitter follower, 6.132
 2N3904, 6.132, 6.204, 6.206
 2N3906, H.39
 PNP transistor, 6.177
 2N3906, 6.177, 6.206, 7.78
 2N3954, N-channel JFET dual op amp, 6.201
 2N3958, 6.201
 2N4117, general purpose JFET diode, 7.78
 2N4121, H.38
 2N4258, H.39
 2N5210, 6.199
 2N5457, JFET diode, 7.77
 2N5457, 7.77-78
 2N5459, 6.204
 2N5911, H.38-39
 2N5911, 6.79
 2SK389 Dual FET, Silicon Monolithic N-
 Channel Junction Type Data Sheet, 6.207
 2SK389, 6.204
 6SL7, 6.206
 6SL7GTB, 6.206
 6SN7GTB, 6.206
 709, 1.104, 6.201
 741, 1.78, 1.103-104, 6.201
 743, 1.78
 744, 1.78
 795, 1.78
 7815, 7.54
 7915, 7.54
 Aavid 5801, 4.64, 6.49
 AMP 5-330808-6, 7.159
 CD4001, 6.171
 CD4011, 6.170-171
 DPAD1, 7.83
 FD333, H.36
 HP5082-4204 PIN Photodiode, 4.59
 J401, 6.201
 JT-16A (Jensen), 6.8
 LF356, 6.199
 LH0033, 6.79
 LM101, 1.104
 LM301A, 6.199
 LM309, 7.54
 LM317, 7.54-55
 LM337, 7.54-55
 Micrel MIC4427, 4.24
 Mini-Circuits T16-6T, 3.36
 MPSA42, 6.206
 MPSA92, 6.206
 P4250, H.38
 PAD1, low leakage diode, 7.83
 PN2222A, 6.194-196, 6.200
 PN2907A, 6.194-196
 PN4117, JFET diode, 7.77
 SD-020-12-001, 4.41
 SM-8, 6.194
 SOT-363, 6.194
 TO-99, metal can packaging, 7.42
 TO92, 6.194
 ZDT651, 6.196
 ZTX652, ZDX653 NPN Silicon Planar Medium
 Power Transistors Data Sheet, 6.207
 ZDT751, 6.195-196
 ZTX752, ZDX753 PNP Silicon Planar Medium
 Power Transistors Data Sheet, 6.207
 ZTX653, 6.195-196
 ZTX753, 6.195-196

▣ OP AMP APPLICATIONS